



# Air solenoid valve VSVA-B-T32H-AH-A2-2AC1

Part number: 547173

**FESTO**



 General operating condition

## Data sheet

| Feature                                                                | Value                                                                                               |
|------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Valve function                                                         | 2x3/2, open/closed, monostable                                                                      |
| Actuation type                                                         | Electrical                                                                                          |
| Valve size                                                             | 18 mm                                                                                               |
| Standard nominal flow rate                                             | 400 l/min                                                                                           |
| Pneumatic working port                                                 | Sub-base, size 18 mm as per ISO 15407-1<br>Connecting plate size 02 according to VDMA 24563<br>G1/8 |
| Operating voltage                                                      | 110V AC                                                                                             |
| Operating pressure                                                     | 0.2 MPa ... 1 MPa                                                                                   |
| Operating pressure                                                     | 2 bar ... 10 bar                                                                                    |
| Structural design                                                      | Piston gate valve                                                                                   |
| Reset method                                                           | Pneumatic spring                                                                                    |
| CE marking (see declaration of conformity)                             | As per EU low voltage directive                                                                     |
| UKCA marking (see declaration of conformity)                           | To UK instructions for EMC                                                                          |
| Degree of protection                                                   | IP65<br>NEMA 4                                                                                      |
| Nominal width                                                          | 5 mm                                                                                                |
| Exhaust air function                                                   | With flow control option                                                                            |
| Sealing principle                                                      | Soft                                                                                                |
| Mounting position                                                      | Any                                                                                                 |
| Conforms to standard                                                   | ISO 15407-1<br>VDMA 24563                                                                           |
| Manual override                                                        | Non-detenting                                                                                       |
| Type of control                                                        | Pilot-controlled                                                                                    |
| Pilot air supply port                                                  | Internal                                                                                            |
| Flow direction                                                         | Non-reversible                                                                                      |
| Symbol                                                                 | 00992808                                                                                            |
| Lap                                                                    | Overlap                                                                                             |
| Signal status display                                                  | LED                                                                                                 |
| Pilot pressure MPa                                                     | 0.3 MPa ... 1 MPa                                                                                   |
| Pilot pressure                                                         | 3 bar ... 10 bar                                                                                    |
| Flow rate of pneumatic valve                                           | 600 l/min                                                                                           |
| Flow rate of pneumatic valve on individual sub-base                    | 450 l/min                                                                                           |
| Optimized flow rate of pneumatic valve pneumatically concatenated flow | 400 l/min                                                                                           |
| Switching time off                                                     | 21 ms                                                                                               |
| On switching time                                                      | 13 ms                                                                                               |
| Duty cycle                                                             | 100%                                                                                                |

| Feature                                   | Value                                                                                |
|-------------------------------------------|--------------------------------------------------------------------------------------|
| Coil characteristics                      | 110 V AC: 50/60 Hz, initial power 2.9 VA, holding power 2.1 VA                       |
| Permissible voltage fluctuations          | -15 % / +10 %                                                                        |
| Operating medium                          | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Information on operating and pilot media  | Operation with oil lubrication possible (required for further use)                   |
| Vibration resistance                      | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance                          | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27                |
| Corrosion resistance class (CRC)          | 0 - No corrosion stress                                                              |
| LABS (PWIS) conformity                    | VDMA24364-B1/B2-L                                                                    |
| Temperature of medium                     | -5 °C ... 50 °C                                                                      |
| Relative air humidity                     | 0 - 90 %                                                                             |
| Noise level                               | 85 dB(A)                                                                             |
| Pilot medium                              | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Ambient temperature                       | -5 °C ... 50 °C                                                                      |
| Max. tightening torque for valve mounting | 1 Nm                                                                                 |
| Product weight                            | 174 g                                                                                |
| Electrical connection                     | Form C<br>With PE conductor<br>as per DIN EN 175301-803                              |
| Type of mounting                          | On sub-base                                                                          |
| Auxiliary pilot air port 12               | Sub-base, size 18 mm as per ISO 15407-1                                              |
| Auxiliary pilot air port 14               | Sub-base, size 18 mm as per ISO 15407-1                                              |
| Pilot exhaust air port 82/84              | Ducted<br>Not ducted as per standard                                                 |
| Pneumatic connection 1                    | Sub-base, size 18 mm as per ISO 15407-1                                              |
| Pneumatic connection 2                    | Sub-base, size 18 mm as per ISO 15407-1                                              |
| Pneumatic connection 3                    | Sub-base, size 18 mm as per ISO 15407-1                                              |
| Pneumatic connection 4                    | Sub-base, size 18 mm as per ISO 15407-1                                              |
| Pneumatic connection 5                    | Sub-base, size 18 mm as per ISO 15407-1                                              |
| Pilot interface                           | as per ISO 15218                                                                     |
| Note on materials                         | RoHS-compliant                                                                       |
| Seals material                            | HNBR<br>NBR                                                                          |
| Housing material                          | Die-cast aluminum                                                                    |
| Material of screws                        | Steel<br>Galvanized                                                                  |