



# Rotary actuator DSM-12-270-CC-A-B

Part number: 547572

FESTO



 General operating condition

## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Size                                     | 12                                                                 |
| Cushioning angle                         | 15 deg                                                             |
| Adjustment range of swivel angle         | 0 deg ... 246 deg                                                  |
| Swivel angle                             | 0 deg ... 246 deg                                                  |
| Permissible stop radius                  | ≥15 mm                                                             |
| Cushioning                               | Pneumatic shock absorber at both ends                              |
| Mounting position                        | Any                                                                |
| Precision adjustment                     | -3 deg                                                             |
| Mode of operation                        | Double-acting                                                      |
| Structural design                        | Rotary vane                                                        |
| Position sensing                         | For proximity sensor                                               |
| Symbol                                   | 00991265                                                           |
| Operating pressure                       | 0.2 MPa ... 1 MPa                                                  |
| Operating pressure                       | 2 bar ... 10 bar                                                   |
| Max. swivel frequency at 6 bar           | 1.5 Hz                                                             |
| Repetition accuracy                      | 0.1 deg                                                            |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:-:-]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 0 - No corrosion stress                                            |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                  |
| Ambient temperature                      | -10 °C ... 60 °C                                                   |
| Max. stop force                          | 90 N                                                               |
| Max. axial force                         | 18 N                                                               |
| Max. radial force                        | 45 N                                                               |
| Theoretical torque at 6 bar              | 1.25 Nm                                                            |
| Permissible mass moment of inertia       | 0.008 kgm <sup>2</sup>                                             |
| Product weight                           | 285 g                                                              |
| Type of mounting                         | With internal thread                                               |
| Pneumatic connection                     | M5                                                                 |
| Note on materials                        | RoHS-compliant                                                     |
| Drive shaft material                     | Steel<br>Nickel-plated                                             |
| Seals material                           | TPE-U(PU)                                                          |
| Housing material                         | Wrought aluminum alloy                                             |