

PRODUCT-DETAILS

5518-2969 B

Socket outlet with earthing pin, with hinged lid, for multiple mounting



General Information	
Product ID	5518-2969 B
EAN	8595017233807
Catalog Description	Socket outlet with earthing pin, with hinged lid, for multiple mounting
Long Description	Socket outlet with earthing pin, with hinged lid, for multiple mounting

Ordering	
EAN	8595017233807
Minimum Order Quantity	1 piece
Customs Tariff Number	85366990

Dimensions	
Product Net Width	62 mm
Product Net Height	106 mm
Product Net Depth / Length	52.7 mm
Product Net Weight	0.1002 kg

Container Information	
Package Level 1 Units	box 24 piece
Package Level 1 Width	0.393 m

5518-2969 B

Package Level 1 Height	0.142 m
Package Level 1 Depth / Length	0.195 m
Package Level 1 Gross Weight	0.11279 kg
Package Level 1 EAN	8595017233807

Technical UL/CSA

.

Short-Circuit Current 0 mA Rating (SCCR)

Additional Information	
Color	White
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	5050 Hz
Material	Plastic
Mounting Type	Surface mounted (plaster)
Number of Phases	1
Product Name	Socket outlet with earthing pin, with hinged lid, for multiple mounting

Product Name Socket outlet with earthing pin, with hinged lid, for multiple mounting
Rated Current (In) 16 A
Rated Voltage (Ur) 250 V

Surface Finishing Surface protection: Untreated Surface finishing: Glossy

Classifications

ETIM 5	EC000125 - Socket outlet
ETIM 6	EC000125 - Socket outlet
ETIM 7	EC000125 - Socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Socket\ Outlets \rightarrow Single\ Socket\ Outlets \rightarrow Single\ Socket\ Outlets \rightarrow Single\ Socket\ Outlets$ $Flush\ Mounted \rightarrow Single\ Socket\ Outlets$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Surface\ Mounted\ Range \rightarrow Surface\ Ranges\ Waterproof\ IP44 \rightarrow Design\ Praktik \rightarrow Single\ Socket\ Outlets$









5518-2969 B 3



