

PRODUCT-DETAILS

5518-2969 S

Socket outlet with earthing pin, with hinged lid, for multiple mounting



| General Information | |
|---------------------|---|
| Product ID | 5518-2969 S |
| EAN | 8595017241819 |
| Catalog Description | Socket outlet with earthing pin, with hinged lid, for multiple mounting |
| Long Description | Socket outlet with earthing pin, with hinged lid, for multiple mounting |

| Ordering | |
|------------------------|---------------|
| EAN | 8595017241819 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85366990 |

| Dimensions | |
|-------------------------------|-----------|
| Product Net Width | 62 mm |
| Product Net Height | 106 mm |
| Product Net Depth / Length | 52.7 mm |
| Product Net Weight | 0.1002 kg |

| Container Information | |
|-----------------------|--------------|
| Package Level 1 Units | box 24 piece |
| Package Level 1 Width | 0.393 m |

5518-2969 S 2

| Package Level 1 Height | 0.142 m |
|-----------------------------------|---------------|
| Package Level 1 Depth / Length | 0.195 m |
| Package Level 1 Gross Weight | 0.11279 kg |
| Package Level 1 EAN | 8595017241819 |

Technical UL/CSA

Short-Circuit Current 0 mA Rating (SCCR)

Additional Information

| Additional information | |
|---------------------------------|---|
| Color | Grey |
| Connection Type | Screw |
| Degree of Protection | IP44 |
| Frequency (f) | 5050 Hz |
| Material | Plastic |
| Mounting Type | Surface mounted (plaster) |
| Number of Phases | 1 |
| Product Name | Socket outlet with earthing pin, with hinged lid, for multiple mounting |
| Rated Current (In) | 16 A |
| Rated Voltage (U _r) | 250 V |
| Surface Finishing | Surface protection: Untreated Surface finishing: Glossy |

Classifications

| ETIM 5 | EC000125 - Socket outlet |
|---------------|--|
| ETIM 6 | EC000125 - Socket outlet |
| ETIM 7 | EC000125 - Socket outlet |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Socket\ Outlets \rightarrow Single\ Socket\ Outlets \rightarrow Single\ Socket\ Outlets \rightarrow Single\ Socket\ Outlets$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Surface\ Mounted\ Range \rightarrow Surface\ Ranges\ Waterproof\ IP44 \rightarrow Design\ Praktik \rightarrow Single\ Socket\ Outlets$









5518-2969 S 3



