

PRODUCT-DETAILS

5598-2929H

Socket outlet with earthing pin, with hinged lid, with surge protection



Product image
not available

General Information

Product ID	5598-2929H
EAN	8592624054276
Catalog Description	Socket outlet with earthing pin, with hinged lid, with surge protection
Long Description	Socket outlet with earthing pin, with hinged lid, with surge protection

Ordering

EAN	8592624054276
Minimum Order Quantity	1 piece
Customs Tariff Number	85366990

Dimensions

Product Net Width	62 mm
Product Net Height	93.5 mm
Product Net Depth / Length	52.7 mm
Product Net Weight	0.1131 kg

Container Information

Package Level 1 Units	packet 1 piece
Package Level 1 Width	0.088 m

Package Level 1 Height	0.063 m
Package Level 1 Depth / Length	0.11 m
Package Level 1 Gross Weight	0.15757 kg
Package Level 1 EAN	8592624054276

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0 mA
-------------------------------------	------

Additional Information

Color	Brown
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50...50 Hz
Material	Plastic
Mounting Type	Surface mounted (plaster)
Number of Phases	1
Product Name	Socket outlet with earthing pin, with hinged lid, with surge protection
Rated Current (I _n)	16 A
Rated Voltage (U _r)	230 V
Surface Finishing	Surface protection: Untreated Surface finishing: Glossy

Classifications

ETIM 5	EC000125 - Socket outlet
ETIM 6	EC000125 - Socket outlet
ETIM 7	EC000125 - Socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switch Assortments → Socket Outlets → Socket Outlets with Advanced Functionality → Socket Outlets with Advanced Functionality - Flush Mounted → Socket Outlets with Advanced Functionality

Low Voltage Products and Systems → Switch Assortments → Surface Mounted Range → Surface Ranges Waterproof IP44 → Design Praktik → Socket Outlets with Advanced Functionality



