

Radial gripper HGRT-20-A-G2

Part number: 563907

FESTO



 General operating condition

Data sheet

Feature	Value
Size	20
Max. interchangeability	≤ 0.2 mm
Max. gripper jaw angular play ax, ay	≤ 0.1 deg
Max. opening angle	180 deg
Rotational symmetry	≤ 0.2 mm
Pneumatic gripper repetition accuracy	≤ 0.02 mm
Number of gripper jaws	2
Mounting position	Any
Mode of operation	Double-acting
Gripper function	Radial
Gripping force backup	During closing
Structural design	Positively driven motion sequence
Position sensing	For proximity sensor For inductive proximity sensors
Symbol	00991895
Operating pressure	4 bar ... 8 bar
Max. operating frequency of pneumatic gripper	≤ 3 Hz
Min. opening time at 6 bar	372 ms
Min. closing time at 6 bar	295 ms
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	5 °C ... 60 °C
Mass moment of inertia	0.81 kgcm ²
Maximum force on gripper jaw Fz, static	100 N
Maximum torque on gripper jaw, My static	6.2 Nm
Maximum torque on gripper jaw, Mz static	0.5 Nm
Relubrication interval for guidance elements	10 MioCyc
Product weight	320 g
Type of mounting	With internal thread and centering sleeve
Pneumatic connection	M5
Note on materials	RoHS-compliant
Housing material	Wrought aluminum alloy, smooth-anodized
Gripper jaw material	Hardened steel