


# Filter MS9-LF-G-CUV

Part number: 564109

FESTO



 General operating condition

## Data sheet

| Feature                          | Value                                                      |
|----------------------------------|------------------------------------------------------------|
| Size                             | 9                                                          |
| Series                           | MS                                                         |
| Mounting position                | Vertical +/- 5°                                            |
| Grade of filtration              | 5 µm                                                       |
| Condensate drain                 | Fully automatic                                            |
| Structural design                | Sinter filter with centrifugal separator                   |
| Degree of condensate separation  | >75 %                                                      |
| Symbol                           | 00991520                                                   |
| Operating pressure               | 2 bar ... 12 bar                                           |
| Operating medium                 | Compressed air as per ISO 8573-1:2010 [7:9:-]<br>Inert gas |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress                              |
| LABS (PWIS) conformity           | VDMA24364-B1/B2-L                                          |
| Storage temperature              | 5 °C ... 60 °C                                             |
| Air quality class at the output  | Compressed air as per ISO 8573-1:2010 [6:8:4]              |
| Temperature of medium            | -10 °C ... 60 °C                                           |
| Ambient temperature              | -10 °C ... 60 °C                                           |
| Pore size                        | 5 µm                                                       |
| Product weight                   | 2000 g                                                     |
| Type of mounting                 | With accessories                                           |
| Covering material                | PA-reinforced                                              |
| Material of spin disc            | POM                                                        |
| Material of filter support       | POM                                                        |
| Note on materials                | RoHS-compliant                                             |
| Material of sub-base             | Die-cast aluminum                                          |
| Material of mounting bracket     | Die-cast aluminum                                          |
| Compressed air filter material   | PE                                                         |
| Housing material                 | Die-cast aluminum                                          |
| Module connector material        | Die-cast aluminum                                          |
| Material of bowl                 | Wrought aluminum alloy                                     |
| Shell sealing material           | NBR                                                        |
| Inspection window material       | PA                                                         |
| Separating disc material         | POM                                                        |