

PSEN sg2c-3LPC unit

570808




Safety gate system includes safe interlocking device with guard locking. According to DIN EN60947-5-3. For applications up to SIL CL3 or Ple. Device type: 1. illuminated push button 2. push button 3. blind cover Scope of delivery: Sensor unit with push buttons including color covers and escape release pin as well as actuator (bolt) for doors with hinges left or right."

Datos técnicos

Certificaciones:	CE;cULus Listed;TÜV;FCC
Principio sensor:	Transpondedor
Tipo de encriptado:	encriptados
Fuerza retención dirección de giro:	2000 N
Número de salidas OSSD:	2
Número de entradas:	2
Tipo de borne:	Federzugklemme steckbar
Tensión alimentación (V):	24,0
Tipo de tensión de alimentación:	DC
Consumo de energía DC:	2.0 W
Número de pulsador:	2
Grado de protección, carcasa:	IP54
Número elementos de mando:	2
Dimensión Ancho:	200.0 mm
Dimensión de altura:	465.0 mm
Dimensión Profundidad:	108.0 mm
Peso bruto:	2950 g
Peso neto:	2570 g
Temperatura ambiente:	-20 - 55 °C

Accesorios opcionales



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)