

## PSEN sg2c-5LPKLE-M12/5 2.2 unit

570884



Safety gate system, safe interlock and safe guard locking device For applications up to SIL CL 3 and PL e. Coding: fully coded. 5 pushbuttons: 1. Illuminated pushbutton for activating the safety gate; 2. Push button for accessing & interlocking the safety gate; 3. Key switch (3 positions) 4. Illuminated pushbutton; 5. E-STOP pushbutton M12/5 connection with enable switch Delivery scope: Sensing device with pushbuttons incl. colour caps and Escape release bar and actuator for right or left hinged gates.

### Datos técnicos


|                                     |                         |
|-------------------------------------|-------------------------|
| Certificaciones:                    | CE;cULus Listed;TÜV;FCC |
| Principio sensor:                   | Transpondedor           |
| Tipo de encriptado:                 | unicat                  |
| Fuerza retención dirección de giro: | 2000 N                  |
| Número de salidas OSSD:             | 2                       |
| Número de entradas:                 | 2                       |
| Tipo de borne:                      | Federzugklemme steckbar |
| Tensión alimentación (V):           | 24,0                    |
| Tipo de tensión de alimentación:    | DC                      |
| Consumo de energía DC:              | 2.0 W                   |
| Número de pulsador:                 | 2                       |
| Grado de protección, carcasa:       | IP54                    |
| Número parada de emergencia:        | 1                       |
| Número elementos de mando:          | 4                       |
| Dimensión Ancho:                    | 200.0 mm                |
| Dimensión de altura:                | 568.0 mm                |
| Dimensión Profundidad:              | 108.0 mm                |
| Peso bruto:                         | 3060 g                  |
| Peso neto:                          | 2690 g                  |
| Temperatura ambiente:               | -20 - 55 °C             |

## Accesorios opcionales



401110

PIT en1.0p-5m-s



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)