


# Pressure transmitter SPTE-V1R-S6-V-2.5K

Part number: 571475

**FESTO**



 General operating condition

## Data sheet

| Feature                                      | Value                                                 |
|----------------------------------------------|-------------------------------------------------------|
| Symbol                                       | 00992257                                              |
| Certification                                | RCM compliance mark<br>c UL us - Recognized (OL)      |
| CE marking (see declaration of conformity)   | As per EU EMC directive<br>As per EU RoHS directive   |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions |
| Certificate issuing authority                | UL E322346                                            |
| Note on materials                            | RoHS-compliant                                        |
| Measured variable                            | Relative pressure                                     |
| Method of measurement                        | Piezoresistive pressure sensor                        |
| Pressure measuring range initial value       | 0 MPa                                                 |
| Pressure measuring range initial value       | 0 bar                                                 |
| Pressure measuring range initial value       | 0 psi                                                 |
| Pressure measuring range end value           | -0.1 MPa                                              |
| Pressure measuring range end value           | -1 bar                                                |
| Pressure measuring range end value           | -14.5 psi                                             |
| Overload pressure                            | 0.5 MPa                                               |
| Overload pressure                            | 5 bar                                                 |
| Overload pressure                            | 72.5 psi                                              |
| Operating medium                             | Compressed air as per ISO 8573-1:2010 [7:4:4]         |
| Information on operating and pilot media     | Operation with oil lubrication possible               |
| Temperature of medium                        | 0 °C ... 50 °C                                        |
| Ambient temperature                          | 0 °C ... 50 °C                                        |
| Accuracy in ± % FS                           | 3 %FS                                                 |
| Repetition accuracy in ± %FS                 | 0.3 %FS                                               |
| Temperature co-efficient in ± %FS/K          | 0.05 %FS/K                                            |
| Analog output                                | 0 - 10 V                                              |
| Rise time                                    | 1 ms                                                  |
| Min. load resistance of voltage output       | 15 kOhm                                               |
| Short-circuit protection                     | For all electrical connections                        |
| DC operating voltage range                   | 18 V ... 30 V                                         |
| Reverse polarity protection                  | for all electrical connections                        |
| Electrical connection                        | 3-wire<br>Cable<br>Open end                           |
| Cable length                                 | 2.5 m                                                 |

| Feature                                            | Value                                                              |
|----------------------------------------------------|--------------------------------------------------------------------|
| Type of mounting                                   | Plug-in                                                            |
| Mounting position                                  | Any                                                                |
| Pneumatic connection                               | Push-in sleeve QS-6                                                |
| Product weight                                     | 35 g                                                               |
| Housing material                                   | PA-reinforced                                                      |
| Sealing ring material                              | FPM                                                                |
| Degree of protection                               | IP40                                                               |
| Corrosion resistance class (CRC)                   | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                     |
| Suitability for the production of Li-ion batteries | Suitable for battery production with reduced Cu/Zn/Ni values (F1a) |
| Cleanroom class                                    | Class 4 according to ISO 14644-1                                   |