

LIGHTNING ARRESTER TYPE 1 REQUIREMENT
CATEGORY B,
UC 350V PLUG-IN PROTECTION BLOCKS 3-POLE,
3+0 CIRCUIT FOR TNC-SYSTEMS W. REMOTE DISPLAY



Similar to image

Technical data:		
product brand name		SETRON
Design of the product		Lightning arrester
Operating voltage		
• with AC / nominal value	V	240
Continuous operating voltage / with AC / maximum	V	350
Supply voltage frequency	Hz	50 ... 60
Protection level	kV	1.5
Apparent power consumption / in standby mode	mVA	4
Impulse discharge current		
• for 1-phase / at (8/20) µs / maximum	kA	25
• for 3-phase / at (8/20) µs / rated value	kA	75
Surge withstand capability / at 6 kV / at (8/20) µs	kV	1.5
Dead time	ns	100
Degree of pollution		2
Overvoltage category / according to IEC 61010-1		III
Product component / fuse		No
Protection class IP		IP20
Insulation material		PBT

Combustibility class acc. to UL 94		V0
Type of fusing / at input for supply voltage		315A125A* gl/gG (*with feed-through wiring)
Short-circuit firmness		For 315gL: 50 kA rms
Ambient temperature	°C	-40 ... +80
Mounting type • for rigid conductor / maximum • for rigid conductor / minimum • maximum • minimum	mm ² mm ² mm ² mm ²	Rail-mountable NS 35 35 2.5 25 2.5
Connectable AWG conductor cross-section / as coded AWG spec. / for grounding • finely stranded	mm ²	13 ... 2
Design of the thread		M5
Product component / remote-signaling contact		Yes
Size of the surge arrester		6MW
SPD classification / according to EN 61643-11 • Test Class I, Type 1 • test class II type 2 • Test Class III, Type 3		Yes No No
Signal design		Defect signaling contact
Design of the switching function		1 CO
Design of the electrical connection		M2 screw thread
Stripped length / for remote signaling contact	mm	7
Net weight	g	1,374

Certificates/approvals:

General Product Approval

Declaration of
Conformity

other



[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SD7413-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SD7413-1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD7413-1

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Jun 30, 2014