



LIGHTNING ARRESTER TYPE 1, UN 240/400V,
UC 335/264V A.C.,
PLUGGABLE PROTECTION MODULES,
3+1 CIRCUIT (TN-S, TT),
WIDTH 72MM REMOTE CONTROL

Similar to image

Technical data:		
product brand name		SETRON
Design of the product		Lightning arrester
Operating voltage		
• with AC / nominal value	V	240
Continuous operating voltage / with AC / maximum	V	335
• note		(L-N)
Supply voltage frequency	Hz	50 ... 60
Protection level		
• between N and L	kV	1.2
• between PE and N and/or L	kV	1.7
• between PE and L / for useful signal	kV	2
Apparent power consumption / in standby mode	mVA	268
Impulse discharge current		
• for 1-phase / at (8/20) µs / maximum	kA	12.5
• between N and PE / for 1-phase / at (8/20) µs / rated value	kA	50
• between L and N / for 1-phase / at (8/20) µs / maximum	kA	50
• between N and PE / for 1-phase / at (8/20) µs / maximum	kA	50
Surge withstand capability / at 6 kV / at (8/20) µs	kV	1.7

Residual voltage		
• at (8/20) µs	kV	1.2
• between L and PE / at (8/20) µs	kV	2
• between L and PE / at (8/20) µs	kV	0.6
• at 10 kA / at (8/20) µs	kV	1.1
• between L and PE / at 10 kA / at (8/20) µs	kV	1.5
• between N and PE / at 10 kA / at (8/20) µs	kV	0.5
• at 5 kA / at (8/20) µs	kV	1
• between L and PE / at 5 kA / at (8/20) µs	kV	1.2
• between N and PE / at 5 kA / at (8/20) µs	kV	0.5
• at 3 kA / at (8/20) µs	kV	0.9
• between L and PE / at 3 kA / at (8/20) µs	kV	1.1
• between N and PE / at 3 kA / at (8/20) µs	kV	0.4
Dead time	ns	25
Degree of pollution		2
Overvoltage category / according to IEC 61010-1		III
Product component / fuse		No
Protection class IP		IP20
Combustibility class acc. to UL 94		V0
Type of fusing / at input for supply voltage		160A80AGL/gG (*with feed-through wiring)
Short-circuit firmness		25 kA rms
Ambient temperature	°C	-40 ... +80
Mounting type		Rail-mountable NS 35
• for rigid conductor / maximum	mm²	35
• for rigid conductor / minimum	mm²	1.5
• maximum	mm²	25
• minimum	mm²	1.5
Connectable AWG conductor cross-section / as coded AWG spec. / for grounding		
• finely stranded	mm²	15 ... 2
Design of the thread		M5
Product component / remote-signaling contact		Yes
Size of the surge arrester		4MW
SPD classification / according to EN 61643-11		
• Test Class I, Type 1		Yes
• test class II type 2		No
• Test Class III, Type 3		No
Signal design		Defect signaling contact
Design of the switching function		1 CO
Design of the electrical connection		M2 screw thread

Stripped length / for remote signaling contact	mm	7
Net weight	g	677

Certificates/approvals:

General Product Approval



GOST



KEMA

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SD7414-3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SD7414-3/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD7414-3

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Jun 30, 2014