



SURGE ARRESTER TYPE 2 REQUIREMENT CATEGORY C,
UC 350V PLUG-IN PROTECTION BLOCKS 3-POLE,
3+0 CIRCUIT FOR TNC SYSTEMS W. REMOTE DISPLAY

Similar to image

Technical data:		
product brand name		SENTRON
Design of the product		Surge arrester
Operating voltage		
• with AC / nominal value	V	240
Continuous operating voltage / with AC / maximum	V	350
Supply voltage frequency	Hz	50 ... 60
Protection level	kV	1.4
Apparent power consumption / in standby mode	mVA	3.5
Impulse discharge current		
• for 1-phase / at (8/20) µs / maximum	kA	20
• for 3-phase / at (8/20) µs / rated value	kA	60
• between L and N / for 1-phase / at (8/20) µs / maximum	kA	40
• for 3-phase / at (1.2/50) µs / maximum	kA	120
Residual voltage		
• at (8/20) µs	kV	1.4
• at 10 kA / at (8/20) µs	kV	1.2
• at 5 kA / at (8/20) µs	kV	1.1
• at 3 kA / at (8/20) µs	kV	1

Voltage Protection Rating (VPR) / according to UL 1449	V	900
Limit voltage		
• at puls curve shape C3 / at (20 kV/10 kA) / according to IEEE C 62.41 and BS 6651	kV	1.2
• at puls curve shape C2 / at (10 kV/5 kA) / according to IEEE C 62.41 and BS 6651	kV	1.1
• at puls curve shape B3/C1 / at (6 kV/3 kA) / according to IEEE C 62.41 and BS 6651	kV	1
Dead time	ns	25
Degree of pollution		3
Overvoltage category / according to IEC 61010-1		IV
Product component / fuse		No
Protection class IP		IP20
Insulation material		PBT / PA 6.6
Combustibility class acc. to UL 94		V0
Type of fusing / at input for supply voltage		125 gL/gG
Short-circuit firmness		For 125gL: 25 kA rms
Ambient temperature	°C	-40 ... +80
Mounting type		Rail-mountable NS 35
• for rigid conductor / maximum	mm ²	35
• for rigid conductor / minimum	mm ²	0.5
• maximum	mm ²	25
• minimum	mm ²	0.5
Connectable AWG conductor cross-section / as coded AWG spec. / for grounding		
• finely stranded	mm ²	20 ... 2
Product component / remote-signaling contact		Yes
Size of the surge arrester		3WM
SPD classification / according to EN 61643-11		
• Test Class I, Type 1		No
• test class II type 2		Yes
• Test Class III, Type 3		No
Signal design		Defect signaling contact
Design of the switching function		1 CO
Design of the electrical connection		M2 screw thread
Stripped length / for remote signaling contact	mm	7
Net weight	g	371

Certificates/approvals:

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SD7463-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/5SD7463-1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD7463-1

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Jun 30, 2014