


SURGE PROTECTION FOR ANALOG AND DIGITAL
TELECOMMUNICATIONS INTERFACES,
CONNECTION: RJ45(RJ12/RJ11)



Model		
product brandname		SETRON
Product designation		Surge protection device
Design of the product		Surge arrester 5SD7 for measuring and control technology
Design of the product / explosion-proof design		No
General technical data		
Break time		
• between L and N / for symmetrical circuit	ns	100
• between L or N and PE / for symmetrical circuit	ns	100
Insertion loss / for symmetrical circuit		
• with characteristic wave impedance 150 ohm / up to 400 kHz / typical	dB	0.3
• with characteristic wave impedance 600 ohm / up to 70 kHz / typical	dB	0.3
Power pulse current / at (10/1000) µs	A	150
Capacity / between switched connecting terminals		
• for symmetrical circuit	nF	0.02
• for asymmetrical circuit	pF	20

Protection level • between L or N and PE / for symmetrical circuit / with spike / with pulse curve shape C2 / at (10 kV/5 kA) / acc. to IEC 61643-21 • with pulse curve shape C2 / at (10 kV/5 kA) / to signal ground / acc. to IEC 61643-21	V	250
	V	250
Overvoltage category		II

Voltage

Continuous operating voltage • at DC / maximum	V	185
Residual voltage / between L and L • for rated discharge current / for symmetrical circuit	V	120
Voltage limitation / of the output voltage • between L and L / at rate of voltage rise 1 kV/μs / for spike or statistical distribution in relation to danger level / for symmetrical circuit • between L and PE / for asymmetrical circuit / at rate of voltage rise 1 kV/μs / for spike or statistical distribution in relation to danger level	V	250
	V	250

Protection class

Protection class IP		IP20
----------------------------	--	------

Electricity

Discharge current • between L and L / for symmetrical circuit / at (8/20) μs / Rated value • between sum of all L and PE / for asymmetrical circuit / at (8/20) μs / Rated value	A	5 000
	kA	5
Consumed current / Rated value	A	0.38
Protection level / between L and N / for symmetrical circuit • with spike / with pulse curve shape C2 / at (10 kV/5 kA) / acc. to IEC 61643-21	V	250

Main circuit

Operating voltage • rated value / maximum	V	185
---	---	-----

Product details

Product component / remote-signaling contact		No
--	--	----

Product function

Product function / Surge arrester monitoring		No
--	--	----

Connections

Type of electrical connection		RJ45
-------------------------------	--	------

Mechanical Design

Height	mm	25
Width	mm	102
Depth	mm	65
Net weight	g	290
Material / of the enclosure		ZnAl4Cu1

Environmental conditions

Degree of pollution		2
Ambient temperature		
• during operation / minimum	°C	40
• during operation / maximum	°C	85

Certificates

Equipment marking		
• acc. to DIN EN 61346-2		F
• acc. to DIN EN 81346-2		F

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SD7581-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SD7581-2/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD7581-2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

10/14/2016