



NEOZED-FUSE LINK 400V GL/GG,GR.D02,
40A, COLLAPSIBLE BOX

Similar to image

Technical data:

Color coding of the fuse link		black
Current / for AC / rated value	A	40
Size of the fallback-system / acc. to DIN EN 60269-1		D02
Supply voltage • for AC / rated value	V	400
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	50
Ambient temperature • minimum • maximum	°C °C	-5 40

Certificates/approvals:

General Product Approval	Test Certificates	other
 GOST	 VDE	Special Test Certificate Type Test Certificates/Test Report Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SE2340/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2340

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)



last change:

Nov 4, 2012