

Miniature circuit breaker 400 V 10kA, 2-pole, C, 63 A



| Model                                                |                                |
|------------------------------------------------------|--------------------------------|
| Product brand name                                   | SENTRON                        |
| Product designation                                  | Miniature circuit breaker      |
| Design of the product                                | 5SL miniature circuit breakers |
| General technical data                               |                                |
| Number of poles                                      | 2                              |
| Number of poles / Note                               | 2P                             |
| (tripping characteristic class)                      | C                              |
| circuit-breaker / Design                             | 5SL4                           |
| Mechanical service life (switching cycles) / typical | 10 000                         |
| Overvoltage category                                 | 3                              |
| Voltage                                              |                                |
| Type of voltage                                      | AC                             |
| Insulation voltage                                   | 440 V                          |
| • with multi-phase operation / at AC / rated value   |                                |
| Supply voltage                                       |                                |
| Supply voltage / at AC / rated value                 | 400 V                          |
| Supply voltage frequency / rated value               | 50 Hz                          |

|                                                                                             |                                      |
|---------------------------------------------------------------------------------------------|--------------------------------------|
| Protection class                                                                            |                                      |
| Protection class IP                                                                         | IP20, with connected conductors      |
| (energy limitation class)                                                                   | 3                                    |
| Switching capacity                                                                          |                                      |
| Switching capacity current                                                                  |                                      |
| • acc. to EN 60898 / rated value                                                            | 10 kA                                |
| • acc. to IEC 60947-2 / rated value                                                         | 10 kA                                |
| Dissipation                                                                                 |                                      |
| Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 5 W                                  |
| Electricity                                                                                 |                                      |
| Tripping residual / rated value / derated current / at 40 Cel                               | 59.67 A                              |
| Current / at AC / rated value                                                               | 63 A                                 |
| Main circuit                                                                                |                                      |
| Operating voltage                                                                           |                                      |
| • at DC / rated value / maximum                                                             | 60 V                                 |
| • with multi-phase operation / at AC / maximum                                              | 440 V                                |
| Suitability for operation                                                                   | Residential buildings/infrastructure |
| Product details                                                                             |                                      |
| Product feature / Touch protection                                                          | Yes                                  |
| Product feature                                                                             |                                      |
| • halogen-free                                                                              | Yes                                  |
| • sealable                                                                                  | Yes                                  |
| • silicon-free                                                                              | Yes                                  |
| Product extension / can be installed / supplementary devices                                | Yes                                  |
| Product function                                                                            |                                      |
| Product function / neutral conductor switching                                              | No                                   |
| Number                                                                                      |                                      |
| Number of test cycles / for environmental testing / acc. to IEC 60068-2-30                  | 28                                   |
| Connections                                                                                 |                                      |
| Connectable conductor cross-section / stranded                                              |                                      |
| • minimum                                                                                   | 0.75 mm <sup>2</sup>                 |
| • maximum                                                                                   | 25 mm <sup>2</sup>                   |
| Mechanical Design                                                                           |                                      |
| (height)                                                                                    | 90 mm                                |
| Width                                                                                       | 36 mm                                |

|                       |       |
|-----------------------|-------|
| Depth                 | 76 mm |
| (mounting position)   | any   |
| Installation depth    | 70 mm |
| Number of width units | 2     |
| (net weight)          | 310 g |

#### Environmental conditions

|                                          |                           |
|------------------------------------------|---------------------------|
| Degree of pollution                      | 2                         |
| Influence of the surrounding temperature | +55 °C, max. 95% humidity |
| Ambient temperature                      |                           |
| • minimum                                | -25 °C                    |
| • maximum                                | 55 °C                     |
| • during storage / minimum               | -40 °C                    |
| • during storage / maximum               | 75 °C                     |

#### Certificates

|                          |   |
|--------------------------|---|
| Reference code           |   |
| • acc. to DIN EN 61346-2 | F |
| • acc. to DIN EN 81346-2 | F |

#### General Product Approval

#### Declaration of Conformity

#### Test Certificates



[Miscellaneous](#)



[Miscellaneous](#)

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL4263-7>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SL4263-7>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SL4263-7](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL4263-7)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>



