



Miniature circuit breaker 400 V 10kA, 3-pole, B, 2A

Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
General technical data	
number of poles	3
design of pole	3P
tripping characteristic class	B
mechanical service life (switching cycles) / typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
type of voltage / of the operating voltage	AC
insulation voltage (Ui)	
• with multi-phase operation / at AC / rated value	440 V
Supply voltage	
supply voltage / at AC / rated value	400 V
operating voltage	
• with multi-phase operation / at AC / maximum	440 V
• at DC / rated value / maximum	72 V
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity current	
• acc. to EN 60898 / rated value	10 kA
• acc. to IEC 60947-2 / rated value	10 kA
energy limitation class	3
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.8 W
Current	
operational current	
• at 30 °C / rated value	2 A
• at 40 °C / rated value	1.92 A
• at 45 °C / rated value	1.88 A
• at 55 °C / rated value	1.79 A
• at AC / rated value	2 A
suitability for operation	Residential buildings/infrastructure
Product details	
product component / neutral conductor switching	No

product feature / touch protection	Yes
product feature	
• halogen-free	Yes
• sealable	Yes
• silicon-free	Yes
product extension / installable / supplementary devices	Yes

Connections

connectable conductor cross-section / solid	
• minimum	0.75 mm ²
• maximum	25 mm ²
connectable conductor cross-section / stranded	
• minimum	0.75 mm ²
• maximum	25 mm ²
connectable conductor cross-section / finely stranded / with core end processing	
• minimum	0.75 mm ²
• maximum	25 mm ²
tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m

Mechanical Design

height	90 mm
width	54 mm
depth	76 mm
installation depth	70 mm
number of modular width units	3
mounting position	any
net weight	430 g

Environmental conditions

ambient temperature / during operation	
• minimum	-25 °C
• maximum	55 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	75 °C

Certificates

reference code	
• acc. to DIN EN 61346-2	F
• acc. to IEC 81346-2	F

General Product Approval

Declaration of Conformity



[Miscellaneous](#)



Test Certificates

other

[Miscellaneous](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL4302-6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SL4302-6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL4302-6

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



