

RC UNIT FOR MCB 5SY TYPE AC (WS),
T=70MM 0.3-63A 4POLE IFN 30MA 400V



Similar to image

Technical data:		
mounting position		any
Height	mm	90
Width	mm	124
Depth	mm	77
Design of the product		Instantaneous
Supply voltage / for AC / rated value	V	400
Ambient temperature	°C	-5 ... +45
Ambient temperature during storage	°C	-40 ... +75
Mechanical operating cycles as operating time / typical		10,000
Overvoltage class		III
Supply voltage / for testing equipment / minimum	V	100
Protection against electrical shock		Finger and back-of-hand safe
Position / of power supply cord		top or bottom
Tightening torque with screw-type terminals	N·m	2.5 ... 3
Section de conducteur raccordable solid	mm²	1.5 ... 25

• multibrin	mm ²	1.5 ... 25
Product feature		
• [not supplied - silicon-free]		Yes
• halogen-free		Yes
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30		28
Device tag		
• according to DIN EN 61346-2		F
• according to DIN EN 81346-2		F

Certificates/approvals:

General Product Approval	Declaration of Conformity	other
 CCC	 EG-Konf.	Environmental Confirmations
 GOST	 VDE	

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SM2345-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM2345-0

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Dec 31, 2012