

RC unit for 5SL4, 3-pole, type AC, In: 40 A, 300 mA, Un AC: 400 V



Model	
product brand name	SETRON
General technical data	
number of poles	3
size of installation devices / acc. to DIN 43880	1
mechanical service life (switching cycles) / typical	10 000
overvoltage category	III
Supply voltage	
supply voltage	
• for testing equipment / minimum	195 V
Dissipation	
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	1.9 W
• maximum	5.7 W
Current	
tripping fault current / rated value	300 mA
operational current	
• at 40 °C / rated value	37.2 A
• at 45 °C / rated value	37.2 A
• at 50 °C / rated value	36 A
• at 55 °C / rated value	34.8 A
• at 60 °C / rated value	34 A
• at 65 °C / rated value	33.2 A
• at 70 °C / rated value	32 A
• at AC / rated value	40 A
residual current type	AC
Connections	
connectable conductor cross-section / solid	
• minimum	1.5 mm ²
• maximum	25 mm ²
connectable conductor cross-section / stranded	
• minimum	1.5 mm ²
• maximum	25 mm ²
tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
Mechanical Design	
height	90 mm

width	105 mm
depth	70 mm
installation depth	70 mm
number of modular width units	3
fastening method	REG
mounting position	any
net weight	320 g

Environmental conditions

ambient temperature / during operation	
• minimum	-5 °C
• maximum	45 °C
ambient temperature / during storage	
• minimum permissible	-40 °C
• maximum permissible	75 °C

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[Miscellaneous](#)



[Miscellaneous](#)

Dangerous Good

[Transport Information](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SM2633-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SM2633-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM2633-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



