

Auxiliary current switch 1 CO For MCB 5SL, 5SY, 5SP Incorporated switch 5TL1 RCBO 5SU1, RC 5SV



Model	
Product brand name	SETRON
Product designation	Auxiliary current switch
Design of the product	Mountable
Electrical endurance (switching cycles) / typical	20 000
Protection class IP	IP20
Product details	
Product component	
• Auxiliary switch	Yes
Number of fault signal contacts	0
Number of NC contacts	0
Number of NO contacts	0
Number of CO contacts	1
Product extension	auxiliary switch
Mechanical Design	
Height	90 mm
Width	9 mm
Depth	70 mm

Net weight	51 g
------------	------

Environmental conditions

Ambient temperature / during operation	
• minimum	-25 °C
• maximum	55 °C
Ambient temperature / during storage	
• minimum permissible	-40 °C
• maximum permissible	75 °C

Certificates

General Product Approval	Declaration of Conformity	other	Railway
 CCC	 UR	 VDE	 EG-Konf.
		Miscellaneous	Vibration and Shock

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3016>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3016>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3016

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



