


PIN BUSBAR,
10 SQMM CONNECTION: 3 PHASE/N + 8XPHASE SAFE-
TO-TOUCH FOR 1F,4-POLE + 8LS,
1-POLE



Similar to image

Technical data:

Busbar design		laminated
Length	mm	210
Width	mm	9.2
Operating current / rated value	A	63
Thickness / of busbar	mm	15.2
Material / of the busbar		SF-Cu F 24
Product property / flexible		No
Traitement de surface / étamé		No

Certificates/approvals:

General Product Approval	other
--------------------------	-------



[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/5ST3624/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3624

CAX-Online-Generator

<http://www.siemens.com/cax>



¹⁾ Pin spacings in MW (Modular widths, 1 MW = 18 mm).

last change:

Nov 29, 2012