

PIN BUSBAR, 10SQMM 56MW, 4PHASES,
SLICEABLE FOR MCB 2P AND RCBO 1P+N SAFE TO
TOUCH WITHOUT END CAPS




Figure similar

Model		
product brand name		SETRON
Product designation		Pin busbar
Design of the product		PIN BB 10mm², 56MW, 4P, CAN BE CUT
Busbar design		laminated
General technical data		
Surface processing / tin-plated		No
Main circuit		
Operating current / Rated value	A	63
Product details		
Product property / flexible		Yes
Mechanical Design		
Width	mm	21.4
Length	mm	1 000
Thickness / of busbar	mm	17.3
Net weight	g	574.61
Material / of the busbar		SF-Cu F 24



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5ST37702>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5ST37702/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST37702

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>



last modified:

27.10.2015