

RCBO, I_{cn}: 10 kA, 2P, type A, 30 mA, B char., I_n: 32 A, U_n AC: 110 V



Model	
product brand name	SENTRON
product designation	RCBO
design of the product	Instantaneous
General technical data	
number of poles	2
number of poles / note	2P
number of poles / with protection	2
tripping characteristic class	B
mechanical service life (switching cycles) / typical	10 000
circuit-breaker / Design	5SU1
overvoltage category	III
degree of pollution	2
Voltage	
surge current resistance / at (8/20) μs	1 kA
Supply voltage	
type of voltage	AC
operating current / at AC / rated value	32 A

supply voltage	
• at AC / rated value	110/120 V
• for testing equipment / minimum	100 V
operating frequency	50 Hz
supply voltage frequency / rated value	50 Hz

Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors

Switching capacity	
breaking capacity short-circuit current (I _{cn}) / according to EN 61009-1 / rated value	10 kA
switching capacity current	
• acc. to EN 60898 / rated value	10 kA
• acc. to IEC 60947-2 / rated value	15 kA
rated residual switching capacity (I _{Δm}) / according to IEC 61009-1	10 kA
energy limiting class	3

Current	
tripping residual current / rated value	30 mA
Tripping residual / rated value / derated current	
• at 30 Cel	32 A
• at 40 Cel	30.4 A
• at 45 Cel	29.76 A
• at 50 Cel	28.8 A
• at 55 Cel	27.84 A
• at 60 Cel	27.2 A
• at 65 Cel	25.92 A
• at 70 Cel	24.64 A
type of fault current	A

Product details	
product function / neutral conductor switching	Yes
product feature / touch protection	Yes
product feature	
• halogen-free	Yes
• silicon-free	Yes

Connections	
connectable conductor cross-section / solid	
• minimum	0.75 mm ²
• maximum	35 mm ²
connectable conductor cross-section / stranded	
• minimum	0.75 mm ²

• maximum	35 mm ²
connectable conductor cross-section / finely stranded / with core end processing	
• minimum	0.75 mm ²
• maximum	25 mm ²
tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
position / of power supply cord	Either top or bottom

Mechanical Design

height	90 mm
width	54 mm
depth	77 mm
installation depth	70 mm
number of width units	3
mounting position	any
net weight	434 g

Environmental conditions

influence of the surrounding temperature	Max. 95% humidity
ambient temperature	
• minimum	-25 °C
• maximum	55 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	75 °C
number of test cycles / for environmental testing / acc. to IEC 60068-2-30	28

Certificates

reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval	Declaration of Conformity	Test Certificates	other	Railway
--------------------------	---------------------------	-------------------	-------	---------

[Miscellaneous](#)



[Special Test Certificate](#)

[Miscellaneous](#)

[Vibration and Shock](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1324-6KX32>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SU1324-6KX32>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1324-6KX32

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



