



RES.CUR.OP.CIR.BR.W.OV.CUR.PROT TYPE F 30MA,
10KA, 1+N-POLE, B 16A

General technical data:		
mounting position		any
Current / for AC / rated value	A	16
Resistance to impulse current / [not supplied - at (8/20) μs]	kA	3
Design of the fault-current type		F
Design of the product		Short-time delayed
Release fault-current / rated value	A	0.03
Number of pitch units for width		2
Degree of pollution		2
Tripping characteristic class		B
Position / of power supply cord		Optionally top or bottom
Mechanical operating cycles as operating time / typical		10,000
Energy limiting class		3
Overvoltage class		3
Product equipment / touch-protection		Yes
Supply voltage		
• for AC / rated value	V	230
• for testing equipment / minimum	V	100
Number of poles /note		
•		1P+N

• with protection		1
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	15
• acc. to EN 60898 / rated value	kA	10
Ambient temperature		
• minimum	°C	-25
• maximum	°C	55
Influence of the surrounding temperature		Max. 95% humidity
Ambient temperature / during storage		
• minimum	°C	-40
• maximum	°C	75
Section de conducteur raccordable		
• solid		
• minimum	mm ²	0.75
• maximum	mm ²	35
• multibrin		
• minimum	mm ²	0.75
• maximum	mm ²	35
• finely stranded / with wire end processing		
• minimum	mm ²	0.75
• maximum	mm ²	25
Tightening torque / with screw-type terminals		
• minimum	N·m	2.5
• maximum	N·m	3
Product feature		
• [not supplied - silicon-free]		Yes
• halogen-free		Yes
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30		26
Item designation		
• according to DIN EN 61346-2		F
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		F

Certificates/approvals:

General Product Approval



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SU1354-3KK16/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1354-3KK16

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 18, 2013