




FI-PROTECTOR LS TYPE A (PSE/SSF),  
D=70MM IFN 30MA, 10KA,  
1+N-POL C 20A SHORT-TIME DELAYED

### General technical data:

|                                                                    |    |                          |
|--------------------------------------------------------------------|----|--------------------------|
| mounting position                                                  |    | any                      |
| Height                                                             | mm | 90                       |
| Width                                                              | mm | 36                       |
| Depth                                                              | mm | 77                       |
| Current / for AC / rated value                                     | A  | 20                       |
| Resistance to impulse current / [not supplied - at (8/20) $\mu$ s] | kA | 3                        |
| Design of the fault-current type                                   |    | AC                       |
| Design of the product                                              |    | Short-time delayed       |
| Release fault-current / rated value                                | A  | 0.03                     |
| Number of pitch units for width                                    |    | 2                        |
| Degree of pollution                                                |    | 2                        |
| Tripping characteristic class                                      |    | C                        |
| Position / of power supply cord                                    |    | Optionally top or bottom |
| Mechanical operating cycles as operating time / typical            |    | 10,000                   |
| Energy limiting class                                              |    | 3                        |
| Overvoltage class                                                  |    | 3                        |
| Product equipment / touch-protection                               |    | Yes                      |
| Supply voltage                                                     |    |                          |
| • for AC / rated value                                             | V  | 230                      |

|                                                                                              |                 |                   |
|----------------------------------------------------------------------------------------------|-----------------|-------------------|
| • for testing equipment / minimum                                                            | V               | 100               |
| <b>Number of poles /note</b>                                                                 |                 |                   |
| •                                                                                            |                 | 1P+N              |
| • with protection                                                                            |                 | 1                 |
| <b>Switching capacity current</b>                                                            |                 |                   |
| • in accordance with IEC 60947-2 / rated value                                               | kA              | 15                |
| • acc. to EN 60898 / rated value                                                             | kA              | 10                |
| <b>Ambient temperature</b>                                                                   |                 |                   |
| • minimum                                                                                    | °C              | -25               |
| • maximum                                                                                    | °C              | 55                |
| <b>Influence of the surrounding temperature</b>                                              |                 | Max. 95% humidity |
| <b>Ambient temperature / during storage</b>                                                  |                 |                   |
| • minimum                                                                                    | °C              | -40               |
| • maximum                                                                                    | °C              | 75                |
| <b>Section de conducteur raccordable</b>                                                     |                 |                   |
| • solid                                                                                      |                 |                   |
| • minimum                                                                                    | mm <sup>2</sup> | 0.75              |
| • maximum                                                                                    | mm <sup>2</sup> | 35                |
| • multibrin                                                                                  |                 |                   |
| • minimum                                                                                    | mm <sup>2</sup> | 0.75              |
| • maximum                                                                                    | mm <sup>2</sup> | 35                |
| • finely stranded / with wire end processing                                                 |                 |                   |
| • minimum                                                                                    | mm <sup>2</sup> | 0.75              |
| • maximum                                                                                    | mm <sup>2</sup> | 25                |
| <b>Tightening torque / with screw-type terminals</b>                                         |                 |                   |
| • minimum                                                                                    | N·m             | 2.5               |
| • maximum                                                                                    | N·m             | 3                 |
| <b>Product feature</b>                                                                       |                 |                   |
| • [not supplied - silicon-free]                                                              |                 | Yes               |
| • halogen-free                                                                               |                 | Yes               |
| <b>Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30</b> |                 | 26                |
| <b>Item designation</b>                                                                      |                 |                   |
| • according to DIN EN 61346-2                                                                |                 | F                 |
| • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750                   |                 | F                 |

Certificates/approvals:

[other](#)**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/lowvoltage/mall>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/5SU1354-7VK20/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SU1354-7VK20](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1354-7VK20)**CAX-Online-Generator**<http://www.siemens.com/cax>

last change:

Feb 18, 2013