

Modular residual current device Type B, 24 V DC,LCD, IDN 30 mA
1A, 0 2000 Hz



Model	
Product brand name	SETRON
Product designation	Modular RCCB device
Design of the product	Digital, type B
Protection class IP / at connection all terminals	IP20
Overvoltage category	III
Control current	
Control supply voltage	
<ul style="list-style-type: none"> at DC / rated value / minimum 	9.6 V
<ul style="list-style-type: none"> at DC / rated value / maximum 	94 V
Auxiliary circuit	
Number of CO contacts / for auxiliary contacts	2
Product function	
Product function / Fault storage	Yes
Connections	
Type of electrical connection	screw-type terminals
Mechanical Design	

Height	85 mm
Width	36 mm
Depth	64 mm
Mounting type	standard rail
Net weight	150 g
Material / of the enclosure	PC
Degree of pollution	3
Ambient temperature	
<ul style="list-style-type: none"> during operation / minimum permissible 	-25 °C
<ul style="list-style-type: none"> during operation / maximum permissible 	55 °C

Certificates

Declaration of Conformity

other



EG-Konf.

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV8111-4KK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV8111-4KK>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8111-4KK

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

