



Model		
product brandname		SENTRON
Main circuit		
Operating frequency / rated value		
• minimum	Hz	50
• maximum	Hz	60
Operating voltage / rated value		
• maximum	V	720
Control current		
Control supply voltage		
• at AC / at 50 Hz / rated value / maximum	V	720
• at AC / at 60 Hz / rated value / maximum	V	720
Auxiliary circuit		
Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Suitability		

Suitability for operation		For AC networks
---------------------------	--	-----------------

Product function		
Product function / Fault storage		No

Connections		
Type of electrical connection		screw-type terminals



Mechanical Design		
Height	mm	32
Width	mm	59
Depth	mm	70
Net weight	g	90

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)
<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SV8701-0KK>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<http://support.automation.siemens.com/WW/view/en/5SV8701-0KK/all>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8701-0KK
- CAX-Online-Generator
<http://www.siemens.com/cax>
- Tender specifications
<http://ausschreibungstexte.siemens.com/tiplv>



last modified:

10/14/2016