



Model	
product brandname	SETRON
Main circuit	
Operating frequency / rated value	
• minimum	50 Hz
• maximum	60 Hz
Operating voltage / rated value	
• maximum	720 V
Control current	
Control supply voltage	
• at AC / at 50 Hz / rated value / maximum	720 V
• at AC / at 60 Hz / rated value / maximum	720 V
Suitability	
Suitability for operation	For AC networks
Product function	
Product function / Fault storage	No
Connections	

Type of electrical connection	screw-type terminals
-------------------------------	----------------------

Mechanical Design

Height	33 mm
Width	100 mm
Depth	79 mm
Net weight	167 g

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SV8702-0KK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SV8702-0KK/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8702-0KK

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

