



CIRCUIT BREAKER T55 230/400V, 6KA,  
1-POLE, B, 6A

**General technical data:**

<b>type of voltage</b>		AC/DC
<b>Mounting depth</b>	mm	55
<b>Current / for AC / rated value</b>	A	6
<b>Tripping characteristic class</b>		B
<b>Supply voltage / for AC / rated value</b>	V	400
<b>Switching capacity current</b>		
• in accordance with IEC 60947-2 / rated value	kA	10
• acc. to EN 60898 / rated value	kA	6
<b>Number of pitch units for width</b>		1
<b>Degree of pollution</b>		3
<b>Overvoltage class</b>		3

**Certificates/approvals:**

**General Product Approval****Declaration of Conformity****Test Certificates****Shipping Approval****other**

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



[other](#)

[Environmental Confirmations](#)

**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/lowvoltage/mall>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5SX2106-6/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SX2106-6](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SX2106-6)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

last change:

Sep 24, 2012