



MINIATURE CIRCUIT-BR. 230/400V 10KA,
1-POLE, B, 20A FOR RAILWAY APPLICATIONS

Similar to image

Technical data:

Type of mounting		Quick assembly system
type of voltage		AC/DC
Height	mm	90
Width	mm	18
Depth	mm	76
mounting position		any
Mounting depth	mm	70
Current / for AC / rated value	A	20
Tripping characteristic class		B
Supply voltage		
• for AC / rated value	V	400
• with single-phase operation / with AC / rated value	V	230
• with multi-phase operation / with AC / rated value	V	400
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	20
• with DC / in accordance with IEC 60947-2 / rated value	kA	15
• acc. to EN 60898 / rated value	kA	10
Breaking capacity short-circuit current (Icn)		

<ul style="list-style-type: none"> • with DC / in accordance with EN 60898-2 	kA	10
<ul style="list-style-type: none"> • with AC / in accordance with UL 1077 and CSA C22.2 No.235 	kA	5
Active power loss / at rated value current / with AC / in warm operating state / per pole	W	2.5
Number of pitch units for width		1
Product feature / sealable		Yes
Degree of pollution		3
Ambient temperature	°C	-40 ... +75
Ambient temperature <ul style="list-style-type: none"> • during storage 	°C	-40 ... +75
Position / of power supply cord		Any
Product property / properties for main switches in accordance with EN 60204-1		Yes
Mechanical operating cycles as operating time / typical		20,000
Overvoltage class		3
Product equipment / touch-protection		Yes
Resistance against shock / according to IEC 60068-2-27		150m/s ² at 11ms half-sine
Insulation voltage <ul style="list-style-type: none"> • with single-phase operation / with AC / rated value • with multi-phase operation / with AC / rated value 	V	250
	V	440
AWG number <ul style="list-style-type: none"> • as encoded connectable conductor cross-section 		14 ... 4
Section de conducteur raccordable <ul style="list-style-type: none"> • solid • multibrin • finely stranded • with wire end processing 	mm ²	0.75 ... 35
	mm ²	0.75 ... 35
	mm ²	0.75 ... 25
Product component <ul style="list-style-type: none"> • combined terminal top • combined terminal bottom 		Yes
		Yes
Tightening torque <ul style="list-style-type: none"> • with screw-type terminals 	N·m	2.5 ... 3
Tightening torque (lbf·in) <ul style="list-style-type: none"> • with screw connection 	lbf·in	22 ... 26
Product feature <ul style="list-style-type: none"> • [not supplied - silicon-free] • halogen-free 		Yes
		Yes
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30		6
Item designation / according to DIN EN 61346-2		F

Certificates/approvals:

General Product Approval

other



[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/5SY4120-6KK11/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY4120-6KK11

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Dec 31, 2012