



CIRCUIT BREAKER 400V 25KA, 3+N-POLE, D, 4A, D=70M

Similar to image

Technical data:		
Type of mounting		Quick assembly system
type of voltage		AC/DC
Height	mm	90
Width	mm	72
Depth	mm	76
mounting position		any
Mounting depth	mm	70
Current / for AC / rated value	A	4
Tripping characteristic class		D
Supply voltage		
• for AC / rated value	V	400
• with multi-phase operation / with AC / rated value	V	400
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	50
• with DC / in accordance with IEC 60947-2 / rated value	kA	15
Breaking capacity short-circuit current (Icn)		
• with AC / in accordance with UL 1077 and CSA C22.2 No.235	kA	5

Active power loss / at rated value current / with AC / in warm operating state / per pole	W	1.2
Number of pitch units for width		4
Product feature / sealable		Yes
Degree of pollution		3
Ambient temperature	°C	-25 ... +55
Ambient temperature during storage	°C	-40 ... +75
Position / of power supply cord		Any
Product property / properties for main switches in accordance with EN 60204-1		Yes
Mechanical operating cycles as operating time / typical		20,000
Overvoltage class		3
Product equipment / touch-protection		Yes
Resistance against shock / according to IEC 60068-2-27		150m/s² at 11ms half-sine
Insulation voltage with multi-phase operation / with AC / rated value	V	440
AWG number as encoded connectable conductor cross-section		14 ... 4
Section de conducteur raccordable - solid - multibrin - finely stranded - with wire end processing	mm² mm² mm²	0.75 ... 35 0.75 ... 35 0.75 ... 25
Product component - combined terminal top - combined terminal bottom		Yes Yes
Tightening torque with screw-type terminals	N·m	2.5 ... 3
Tightening torque (lbf·in) with screw connection	lbf·in	22 ... 26
Product feature [not supplied - silicon-free] - halogen-free		Yes Yes
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30		6
Item designation / according to DIN EN 61346-2		F

Certificates/approvals:

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)



<http://support.automation.siemens.com/WW/view/en/5SY8604-8/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY8604-8

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Dec 31, 2012