

SWITCH 400V 3POLE 40A, T=70MM



Similar to image

Technical data:		
Number of poles		3
Design of the operating mechanism		toggle handle
Type of the driving mechanism / motor drive		No
Design of the electrical connection / for main current circuit		screw-type terminals
Product equipment / interlock		No
Continuous current / rated value	A	40
Type from device		other
Acceptability for application		
• safety cut-out switch		No
• maintenance/repair switch		No
• emergency stop switch		No
Suitability for integration / distribution board		Yes
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		3
Number of changeover contacts / for auxiliary contacts		0
Operating voltage / at 50/60 Hz / for AC / rated value	V	400
Protection class IP		IP20
Acceptability for application		

• main switch	No
• switch disconnecter	Yes
Product extension / optional	
• motor drive	No
• voltage trigger	No
Mounting type	
• front mounting with 4-hole attachment	No
• central front mounting	No

Certificates/approvals:

General Product Approval	Declaration of Conformity	other
 GOST	 EG-Konf.	Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TE2413-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TE2413-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE2413-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Jul 21, 2014