

SWITCH 400V 3+N-POLE 40A, T=70MM



Similar to image

| Technical data:                                                |   |                      |
|----------------------------------------------------------------|---|----------------------|
| Number of poles                                                |   | 4                    |
| Design of the operating mechanism                              |   | toggle handle        |
| Type of the driving mechanism / motor drive                    |   | No                   |
| Design of the electrical connection / for main current circuit |   | screw-type terminals |
| Product equipment / interlock                                  |   | No                   |
| Continuous current / rated value                               | A | 40                   |
| Type from device                                               |   | other                |
| Acceptability for application                                  |   |                      |
| • safety cut-out switch                                        |   | No                   |
| • maintenance/repair switch                                    |   | No                   |
| • emergency stop switch                                        |   | No                   |
| Suitability for integration / distribution board               |   | Yes                  |
| Number of NC contacts / for auxiliary contacts                 |   | 0                    |
| Number of NO contacts / for auxiliary contacts                 |   | 4                    |
| Number of changeover contacts / for auxiliary contacts         |   | 0                    |
| Operating voltage / at 50/60 Hz / for AC / rated value         | V | 400                  |
| Protection class IP                                            |   | IP20                 |
| Acceptability for application                                  |   |                      |

|                                         |     |
|-----------------------------------------|-----|
| • main switch                           | No  |
| • switch disconnecter                   | Yes |
| <b>Product extension / optional</b>     |     |
| • motor drive                           | No  |
| • voltage trigger                       | No  |
| <b>Mounting type</b>                    |     |
| • front mounting with 4-hole attachment | No  |
| • central front mounting                | No  |

#### Certificates/approvals:

| General Product Approval                                                                  | Declaration of Conformity                                                                     | other                                       |
|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------|
| <br>GOST | <br>EG-Konf. | <a href="#">Environmental Confirmations</a> |

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TE2414-0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TE2414-0/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TE2414-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE2414-0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Jul 21, 2014