



Figure similar

| Model                                    |    |                     |
|------------------------------------------|----|---------------------|
| product brand name                       |    | SETRON              |
| Product designation                      |    | On/Off switches     |
| Type of light source                     |    | Not applicable      |
| Mounting type / for light source         |    | Not applicable      |
| Design of the switching function         |    | Switch disconnecter |
| General technical data                   |    |                     |
| Number of poles                          |    | 3                   |
| Number of poles / Note                   |    | 3P+N                |
| Short-circuit current rating             | kA | 10                  |
| Type of voltage                          |    | AC                  |
| Protection class                         |    |                     |
| Protection class IP                      |    | Other               |
| Switching capacity                       |    |                     |
| Switching capacity current / rated value | kA | 0.196               |
| Main circuit                             |    |                     |
| Operating voltage / rated value          | V  | 440                 |

|                                 |   |    |
|---------------------------------|---|----|
| Operating current / rated value | A | 63 |
|---------------------------------|---|----|

## Appearance

|                     |  |                |
|---------------------|--|----------------|
| Color / of the lens |  | Not applicable |
|---------------------|--|----------------|

## Product details

|                                 |  |    |
|---------------------------------|--|----|
| Product component / Signal lamp |  | No |
|---------------------------------|--|----|

## Product function

|                                                            |  |    |
|------------------------------------------------------------|--|----|
| Product function / positive opening (acc. to DIN VDE 0113) |  | No |
|------------------------------------------------------------|--|----|

## Number

|                       |  |   |
|-----------------------|--|---|
| Number of NC contacts |  | 0 |
| Number of NO contacts |  | 3 |
| Number of CO contacts |  | 0 |

## Mechanical Design

|                       |    |    |
|-----------------------|----|----|
| Installation depth    | mm | 70 |
| Number of width units |    | 4  |

|                          |                           |
|--------------------------|---------------------------|
| General Product Approval | Declaration of Conformity |
|--------------------------|---------------------------|



sonstig



## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TL16630>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TL16630/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TL16630](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL16630)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

12.04.2016