## **SIEMENS**

Product data sheet 5TT3423



PHASE SEQUENCE MONITOR, N-TYPE AC 230V 4A

Similar to image

Technical data:			
Design of the electrical connection		screw-type terminals	
Product function			
undervoltage recognition		No	
phase sequence recognition		Yes	
phase disturbance recognition		No	
asymmetry recognition		No	
overvoltage recognition		No	
Measurable voltage / for AC			
• final value	V	400	
• initial value	V	400	
rated operational current le	А	4	
Rated operational voltage Ue	V	250	
Degree of protection / [not supplied - in accordance with DIN EN 60529]		IP20, with connected conductors	
Rated insulation voltage Ui / between spool contact	kV	4	
Contacts / (µ-contact) / AC-11	Α	3	
Operating range / x Uc		0,8 till 1,1	
Rated frequency fn		50/60Hz	

Rated impulse withstand voltage Uimp /drive/contact		> 2,5kV
Rated power loss Pv		9VA (Electronic) ; 0,2VA (contact)
Galvanic isolation / creepage distance and clearance between drive/contact	mm	4
Climate resistance acc. to DIN EN 60068-1		20/60/4
Minimum contact loading		10V; 100mA
Protection class / acc. to DIN EN 61140/VDE 0140-1		II
Design of the electrical connection / jumper socket		No
Type of voltage / for operating		AC
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of change-over switches / for auxiliary contacts		1
Control supply voltage		
• at 60 Hz / at AC / rated value		
• minimum	V	400
• maximum	V	400
• at 50 Hz / at AC / rated value		
• minimum	V	400
• maximum	V	400
Depth	mm	64
Height	mm	90
Width	mm	18
Connection terminals / screw		1
Conductor cross-sections		$2 \times 2,5$ mm² (rigid, max.)
Permissible ambient temperature		-20 till +60°C

## Certificates/approvals:

General Product Approval other



Environmental Confirmations

## Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)


http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/5TT3423/all

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ ...)$ 

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=5TT3423}}$ 



last change: Feb 18, 2013