



SIPLUS ET200S 4DI (1PU=5PCS) -25...+60 DGR C WITH CONFORMAL COATING BASED ON 6ES7131-4BD01-0AA0 . ELECTRONIC MODULE 24V DC WIDTH: 15 MM 5 PCS PER PACKAGING UNIT

Supply voltage	
24 V DC	Yes ; From power module
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
from backplane bus 3.3 V DC, max.	10 mA
from supply voltage L+, max.	Dependent on encoder
Encoder supply	
Output voltage	min. L+ (-0.5 V), under load
Output current	
Output current, rated value	500 mA
Output current, permissible range	0 to 500 mA
Power losses	
Power loss, typ.	0.7 W
Address area	
Address space per module	
with packing	4 bit

without packing	1 byte
Digital inputs	
Number of digital inputs	4
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
Type of input voltage	DC
Rated value, DC	24 V
for signal "0"	-30 to +5 V
for signal "1"	15 to 30 V
Input current	
for signal "1", typ.	7 mA ; at 24 V
Input delay (for rated value of input voltage)	
for standard inputs	
Parameterizable	No
at "0" to "1", min.	2 ms ; typically 3 ms
at "0" to "1", max.	4.5 ms
at "1" to "0", min.	2 ms ; typically 3 ms
at "1" to "0", max.	4.5 ms
Cable length	
Cable length, shielded, max.	1000 m
Cable length unshielded, max.	600 m
Encoder	
Connectable encoders	
2-wire sensor	Yes
Permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostic messages	
Diagnostic functions	No
Diagnostics indication LED	
Group error SF (red)	No
Status indicator digital input (green)	Yes ; per channel
Parameter	
Remark	1 byte
Galvanic isolation	
Galvanic isolation digital inputs	
between the channels	No
between the channels and the backplane bus	Yes

Permissible potential difference	
between different circuits	75 VDC / 60 VAC
Isolation	
Isolation checked with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Extended ambient conditions	
Relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
with condensation, maximum	100 % ; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)
Resistance	
to biologically active substances/conformity with EN 60721-3-3	Yes ; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
to chemically active substances/conformity with EN 60721-3-3	Yes ; Class 3C4 incl. salt spray. The supplied connector covers must remain on the unused interfaces during operation!
to mechanically active substances/conformity with EN 60721-3-3	Yes ; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
Min.	-25 °C ; = Tmin
max.	60 °C ; = Tmax
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	35 g
Status	Jun 16, 2014