



SIPLUS ET200M IM153-2 (*BA02) -40 ... +70 DEGREES C
 START UP TEMP -25 DGR C WITH CONFORMAL
 COATING BASED ON 6ES7153-2BA02-0XB0 . INTERFACE
 ET 200M FOR MAX. 12 S7-300 MODULES WITH
 REDUNDANCY,
 TIME STAMPING FIT FOR ISOCHRON MODE NEW
 FEATURES: USEABLE WITH UP TO 12 MODULES SLAVE
 INITIATIVE FOR DRIVE ES AND SWITCHES ES
 EXTENDED DATA FOR HART SECON- DARY VARIABLES
 OPERATON WITH 64-CHANNEL MODULES 32 SIGNALS /
 SLOT

General information

Vendor identification (VendorID)	801Eh
----------------------------------	-------

Supply voltage

24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
permissible range (ripple included), lower limit (DC)	20.4 V
permissible range (ripple included), upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2,5 A

Mains buffering

Mains/voltage failure buffering time	5 ms
--------------------------------------	------

Input current

Current consumption, max.	600 mA
Rated value at 24 V DC	650 mA
Inrush current, typ.	3 A
I²t	0.1 A²·s

Output voltage

Rated value (DC)	5 V
Rated value, 5 V DC	Yes

Output current	
for backplane bus (5 V DC), max.	1.5 A
Power loss	
Power loss, typ.	5.5 W
Address area	
Addressing volume	
Inputs	244 byte
Outputs	244 byte
Hardware configuration	
Number of modules per DP slave interface, max.	12
Time stamping	
Accuracy	1 ms ; 1ms at up to 8 modules; 10ms at up to 12 modules
Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128 ; Max. 128 signals/station; max. 32 signals/slot
Time format	RFC 1119
Time resolution	0.466 ns
Time interval for transmitting the message buffer if a message is present	1000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting
Interfaces	
Interface physics, RS 485	Yes
Interface physics, FOC	No
PROFIBUS DP	
Node addresses	1 to 125 permitted
automatic detection of transmission rate	Yes
PROFIBUS DP, output current, max.	70 mA
Transmission rate, max.	12 Mbit/s
Transmission procedure	RS 485
SYNC capability	Yes
FREEZE capability	Yes
Direct data exchange (slave-to-slave communication)	Yes ; Sender
PROFIBUS DP	9-pin sub D
1. Interface	
DP slave	
GSD file	SI04801.GSG
automatic baud rate search	Yes
Communication functions	
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170

Isolation	
Isolation tested with	Isolation voltage 500 V
Degree and class of protection	
IP20	Yes
Standards, approvals, certificates	
CE mark	Yes
KC approval	Yes
UL approval	Yes ; File E239877
RCM (former C-TICK)	Yes
FM approval	Yes ; CofC 3028431
EAC (former Gost-R)	Yes
Ambient conditions	
Operating temperature	
min.	-40 °C ; = Tmin
max.	70 °C ; = Tmax; 60 °C @ UL/cUL use
Extended ambient conditions	
relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
at cold restart, minimum	-25 °C
Relative humidity	
with condensation, tested in accordance with IEC 60068-2-38, maximum	100 % ; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
to biologically active substances/conformity with EN 60721-3-3	Yes ; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
to chemically active substances/conformity with EN 60721-3-3	Yes ; Class 3C4 (RH < 75%) incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!
to mechanically active substances/conformity with EN 60721-3-3	Yes ; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Configuration	
Configuration software	
STEP 7	Yes ; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	360 g

