



SIPLUS ET200S TM-E15C26-A1 -40 ... +70 DGR C WITH CONFORMAL COATING BASED ON 6ES7193-4CA50-0AA0 5 PIECES PER PACKAGING UNIT . FOR ELECTRONIC MODULES WIDTH 15MM, SPRING-TYPE TERMINALS 2X6 TERMINAL CONNECTIONS WITH TERMINAL LEAD TO AUX1, AUX1 IN LINE

| General information                                                        |                                                                                                                                                                                                         |
|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Delivery quantity in pieces                                                | 5                                                                                                                                                                                                       |
| Standards, approvals, certificates                                         |                                                                                                                                                                                                         |
| CE mark                                                                    | Yes                                                                                                                                                                                                     |
| Ambient conditions                                                         |                                                                                                                                                                                                         |
| Extended ambient conditions                                                |                                                                                                                                                                                                         |
| relative to ambient temperature-atmospheric pressure-installation altitude | Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m) |
| Relative humidity                                                          |                                                                                                                                                                                                         |
| with condensation, maximum                                                 | 100 % ; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)                                                                                        |
| Resistance                                                                 |                                                                                                                                                                                                         |
| to biologically active substances/conformity with EN 60721-3-3             | Yes ; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!                                     |
| to chemically active substances/conformity with EN 60721-3-3               | Yes ; Class 3C4 incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!                                |
| to mechanically active substances/conformity with EN 60721-3-3             | Yes ; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!                                                                                  |

|                                                            |                 |
|------------------------------------------------------------|-----------------|
| <b>Mechanical and climatic conditions during operation</b> |                 |
| <b>Climatic conditions in operation</b>                    |                 |
| <b>Temperature</b>                                         |                 |
| <b>min.</b>                                                | -40 °C ; = Tmin |
| <b>max.</b>                                                | 70 °C ; = Tmax  |
| <b>Dimensions</b>                                          |                 |
| <b>Width</b>                                               | 15 mm           |
| <b>Height</b>                                              | 157 mm          |
| <b>Depth</b>                                               | 43 mm           |
| <b>Weights</b>                                             |                 |
| <b>Weight, approx.</b>                                     | 70 g            |
| Status                                                     | Jul 23, 2014    |