

SIPLUS ET200S TERMINATING MODULE -25...+60
DEGREES C BASED ON 6ES7193-4JA00-0AA0

Installation type/mounting	
Wall mounting/direct mounting possible	Yes
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Extended ambient conditions	
relative to ambient temperature-atmospheric pressure- installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
with condensation, maximum	100 % ; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)
Resistance	
to biologically active substances/conformity with EN 60721-3-3	Yes ; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
to chemically active substances/conformity with EN 60721-3-3	Yes ; Class 3C4 incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!
to mechanically active substances/conformity with EN 60721-3-3	Yes ; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
min.	-25 °C ; = Tmin
max.	60 °C ; = Tmax
Accessories	
belongs to product	ET 200S
Dimensions	
Width	30 mm
Height	106 mm
Depth	7.5 mm
Weights	
Weight, approx.	50 g

