

SIPLUS ET200M SEPARATOR BUS MOD F;
-25 ... +60 DEGREES C WITH CONFORMAL COATING
BASED ON 6ES7195-7HG00-0XA0



Standards, approvals, certificates

CE mark	Yes
KC approval	Yes
UL approval	Yes ; File E239877
RCM (former C-TICK)	Yes
FM approval	No
EAC (former Gost-R)	Yes

Ambient conditions

Extended ambient conditions

relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m)
--	---

Relative humidity

with condensation, tested in accordance with IEC 60068 -2-38, maximum	100 % ; RH incl. condensation/frost (no commissioning under condensation conditions)
---	--

Resistance

to biologically active substances/conformity with EN 60721-3-3	Yes
to chemically active substances/conformity with EN 60721-3-3	Yes

to mechanically active substances/conformity with EN 60721-3-3	Yes
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
min.	-25 °C ; = Tmin
max.	60 °C ; = Tmax
Accessories	
belongs to product	ET 200M
Weights	
Weight, approx.	10 g
Status	Aug 5, 2014