

Product-type designation	
 SIPLUS SCALANCE X202-2P IRT	
SIPLUS NET SCALANCE X202-2PIRT -25 ... +60 DEGREES C BASED ON 6GK5202-2BH00-2BA3	
Transmission rate	
Transfer rate / 1	10 Mbit/s
Transfer rate / 2	100 Mbit/s
Interfaces	
Number of electrical/optical connections	
• for network components or terminal equipment / maximum	4
Number of electrical connections	
• for network components and terminal equipment	2
• for signaling contact	1
• for power supply	1
• for redundant power supply	1
Design of the electrical connection	
• for network components and terminal equipment	RJ45 port
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
Number of optical interfaces / for optical waveguide / at 100 Mbit/s	2
Design of optical interface / for optical waveguide / at 100 Mbit/s	SC-RJ/POF port
Range / at the optical interface / depending on the optical fiber used	0 ... 0.05 km
design of the removable storage / C-PLUG	Yes
Signal-Inputs/outputs	

Operating voltage / of signaling contacts / at DC / rated value	24 V
Operating current / of signaling contacts / at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of / supply voltage	DC
Supply voltage / external	24 V
• minimum	18 V
• maximum	32 V
Product component / fusing at power supply input	Yes
Type of fusing / at input for supply voltage	1,1 A / 33 V
Consumed current / maximum	0.3 A
Active power loss / at 24 V / for DC	7.2 W
Permitted ambient conditions	
Ambient temperature	
• during operating	-25 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	100 %
Protection class IP	IP30
Design, dimensions and weight	
Design	compact
Width	60 mm
Height	125 mm
Depth	124 mm
Net weight	0.78 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	Yes
Product properties, functions, components / general	
Cascading in the case of a redundant ring / at reconfiguration time of <1~0.3~s	50
Cascading in cases of star structuring	Any (depending only on signal propagation time)
Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• SMTP server	Yes

• Port mirroring	No
• for IRT / PROFINET IO switch	Yes
• PROFINET IO diagnosis	Yes
• switch-managed	Yes
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	No
• IGMP (snooping/querier)	No
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• DCP	Yes
• LLDP	Yes
Product functions / Diagnosis	
Product function	
• Port diagnostics	Yes
• Statistics Packet Size	Yes
• Statistics packet type	Yes
• Error statistics	Yes
Product functions / DHCP	
Product function / DHCP client	Yes
Product functions / Redundancy	
Product function	
• Ring redundancy	Yes
• Redundancy manager	Yes
• Standby redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• Media Redundancy Protocol (MRP)	Yes
• Passive listening	Yes
Product functions / Security	
Protocol / is supported / SSH	Yes
Product functions / Time	
Product function / SICLOCK support	Yes
Protocol / is supported	
• NTP	No

• SNTP	Yes
Standards, specifications, approvals	
Standard	
• for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Verification of suitability	EN 61000-6-2, EN 61000-6-4
• CE mark	Yes
• KC approval	Yes
• Railway application in accordance with EN 50155	No
• Railway application in accordance with EN 50124-1	No
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No
Further Information / Internet Links	
Internet-Link	
• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com
letzte Änderung:	Aug 6, 2014