



SIPLUS NET CSM 1277 -40...+70 °C with conformal coating based on 6GK7277-1AA10-0AA0 Compact Switch Module CSM 1277 connection SIMATIC S7-1200 and up to 3 further nodes to Industrial Ethernet with 10/100 Mbit/s

product type designation	
product brand name	SIPLUS NET
product type designation	CSM 1277
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
ambient conditions	
ambient temperature / in horizontal mounting position / during operation	-40 ... +70 °C; > 60 °C ambient temperature on both sides 25 mm clearance on the left and right of the module to adjacent devices
installation altitude / at height above sea level / maximum	5000 m
relative humidity	
• with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
resistance to biologically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna); class 3B3 on request
• conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
• conformity according to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (Severity degree 3); *
resistance to mechanically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust; *
• conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
environmental category / according to IEC 60721 / note	* The supplied plug covers must remain in place on the unused interfaces during operation!
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
width	75 mm
height	100 mm
depth	45 mm

net weight	0.2 kg				
product functions / management, configuration, engineering					
product function					
• switch-managed	No				
standards, specifications, approvals					
certificate of suitability					
• CE marking	Yes				
standard					
• for EMC interference emission	EN 61000-6-4 (Class A)				
• for immunity to EMC	EN 61000-6-2				
product functions / general					
MTBF	273 a				
reference code					
• according to IEC 81346-2	KF				
• according to IEC 81346-2:2019	KFE				
further information / internet links					
internet link					
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358				
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud				
• to website: Industrial communication	https://www.siemens.com/simatic-net				
• to web page: SiePortal	https://sieportal.siemens.com/				
• to website: Image database	https://www.automation.siemens.com/bilddb				
• to website: CAX-Download-Manager	https://www.siemens.com/cax				
• to website: Industry Online Support	https://support.industry.siemens.com				
security information					
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)				
Approvals / Certificates					
<table> <tr> <td>General Product Approval</td><td>EMV</td></tr> <tr> <td> Manufacturer Declaration   EG-Konf. </td><td> Miscellaneous  RCM </td></tr> </table>		General Product Approval	EMV	Manufacturer Declaration   EG-Konf.	Miscellaneous  RCM
General Product Approval	EMV				
Manufacturer Declaration   EG-Konf.	Miscellaneous  RCM				

last modified:

8/8/2024 