




Figure similar

SIPLUS S7-300 FM350-2 8 CHANNEL FOR MEDIAL STRESS WITH CONFORMAL COATING BASED ON 6ES7350-2AH01-0AE0 . COUNTER MODULE FM 350-2, 8 CHANNELS, 20 KHZ, 24V ENCODER FOR COUNTING, MEASURING FREQUENCIES, SPEED MEASUREMENT, PERIOD DURATION MEASUREMENT AND PROPORTIONING INCL. CONFIG. PACKAGE AND ELECTRONIC DOCU ON CD

Supply voltage

Auxiliary voltage 1L+, load voltage 2L+

• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V

Input current

from load voltage L+ (without load), max.	150 mA
from backplane bus 5 V DC, max.	100 mA

Encoder supply

Type of output voltage	NAMUR-encoder supply: 8.2 V +/-2%
Short-circuit protection	Yes

Output current

• Rated value	200 mA
---------------	--------

Power loss

Power loss, typ.	10 W
------------------	------

Digital inputs

Number of digital inputs	8
--------------------------	---

Functions	1 each for gate start/ gate stop
Input voltage	
• for signal "0"	-3 to +5V
• for signal "1"	11 to 30.2 V
Input current	
• for signal "0", max. (permissible quiescent current)	2 mA
• for signal "1", typ.	9 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	50 µs
Cable length	
• shielded, max.	100 m
Digital outputs	
Number of digital outputs	8
Short-circuit protection	Yes
Limitation of inductive shutdown voltage to	L+ (-40 V)
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
• "0" to "1", max.	300 µs
Switching frequency	
• with resistive load, max.	500 Hz
• with inductive load, max.	0.5 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	2 A
all other mounting positions	
— up to 40 °C, max.	2 A
Cable length	
• shielded, max.	600 m
• unshielded, max.	100 m
Encoder	
Connectable encoders	
• Incremental encoder (asymmetrical)	Yes
• 24 V initiator	Yes
• 24 V directional element	Yes

• NAMUR encoder	Yes
• 2-wire sensor	Yes
NAMUR encoder	
• Number of NAMUR inputs	8
• Input signal	to DIN 19 234
• Input current for signal "0", max.	1.2 mA
• Input current for signal "1", min.	2.1 mA
• Input delay, max.	50 µs
• Input frequency, max.	20 kHz
• Cable length, shielded, max.	100 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
Diagnostic messages	
• Diagnostic functions	Yes; Diagnostic information readable
Diagnostics indication LED	
• Group error SF (red)	Yes
Counter	
Counter input 24 V	
• Number	8; 32 bit or +/-31 bit
• Input voltage for signal "0"	-3 to +5V
• Input voltage for signal "1"	11 to 30.2 V
• Input current for signal "0", max. (permissible quiescent current)	2 mA
• Input current for signal "1", typ.	9 mA
• Input delay, max.	50 µs
• Counting frequency, max.	20 kHz; Incremental encoder: 10 kHz
• Cable length, max.	100 m
Potential separation	
Potential separation digital inputs	
• between the channels and backplane bus	Yes; and shielding
• Between the channels and backplane bus (NAMUR)	yes, against backplane bus and shielding
Potential separation digital outputs	
• between the channels and backplane bus	Yes; and shielding
Potential separation counter	
• between the channels and backplane bus	Yes; and shielding
Standards, approvals, certificates	
CE mark	Yes

UL approval	Yes; File E239877
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes

Ambient conditions

Ambient temperature during operation	
• min.	0 °C; = Tmin
• max.	60 °C; = Tmax

Extended ambient conditions	
• relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)

Relative humidity	
— With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)

Resistance	
— against biologically active substances / conformity with EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
— against chemically active substances / conformity with EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!
— against mechanically active substances / conformity with EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!

Connection method

required front connector	1x 40-pin
--------------------------	-----------

Dimensions

Width	80 mm
Height	125 mm
Depth	120 mm

Weights

Weight, approx.	460 g
-----------------	-------

last modified: 12.09.2015