

SIPLUS HMI TP177B COLOR PN/DP FOR MEDIAL
STRESS BASED ON 6AV6642-0BA01-1AX1



General information

Customer-specific configuration

Yes

Display

Design of display

STN

Screen diagonal

5.7 in

Size

5.7" (120 mm x 90 mm)

Display type

STN, 256 colors

Color type

Colors

Resolution (pixels)

Horizontal image resolution

320

Vertical image resolution

240

Resolution (WxH in pixel)

320 x 240

Backlighting

MTBF backlighting (at 25 °C)

about 50,000 hours

Control elements

Control elements

Touch screen

Operating options

Touch

Connection for mouse/keyboard/barcode reader

USB / USB / USB

Keyboard

System keys	Yes
Numeric/alphabetical input	Yes / Yes
hexadecimal keyboard	Yes
Multi-key operation	No
Touch operation	
Touch screen	analog, resistive
Supply voltage	
Type of supply voltage	DC
Input current	
Rated current	0.24 A
Inrush current A²s	0.5 A²·s
Processor	
Processor	ARM, 200 MHz
Processor type	ARM
Memory	
Type	Flash / RAM
Usable memory for user data	2048 KB usable memory for user data
Time of day	
Clock	
Type	Hardware clock, synchronizable, no battery backup
Hardware clock (real-time clock)	No
Software clock	Yes
Battery-backed	No
Synchronizable	Yes
Interfaces	
Interfaces	RS232 optional, 1 x RS422, 1 x RS485, 1 x Ethernet (RJ45) (max. 12 Mbit/s)
Number of RS 485 interfaces	1
Transmission rate, max.	12 Mbit/s
USB port	1 x USB
PC card slot	No
CF card slot	No
Multimedia card/SD card slot	combined
Special interfaces	No
Industrial Ethernet	
Industrial Ethernet interface	1 x Ethernet (RJ45)
Industrial Ethernet status LED	1
Protocols	
Protocols (terminal link)	

Sm@rtService	Yes
Degree and class of protection	
Front	IP65, NEMA 4x, NEMA 12 (when installed)
IP (at the front)	IP65
Rear	IP20
IP (rear)	IP20
Standards, approvals, certificates	
Certifications	CE
cULus	No
EAC (formerly Gost-R)	No
Suitable for safety functions	No
Marine approval	
Germanischer Lloyd (GL)	No
American Bureau of Shipping (ABS)	No
Bureau Veritas (BV)	No
Det Norske Veritas (DNV)	No
Lloyds Register of Shipping (LRS)	No
Polski Rejestr Statkow (PRS)	No
Use in hazardous areas	
EX zone 2	No
EX zone 22	No
FM Class I Division 2	No
Ambient conditions	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	+/- 35 °
Storage/transport temperature	
Transport, storage	-20 °C to +60 °C
Extended ambient conditions	
Relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
with condensation, maximum	100 % ; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
against biologically active substances / conformity with EN 60721-3-3	Yes ; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!
against chemically active substances / conformity with EN 60721-3-3	Yes ; Class 3C4 incl. salt spray. The supplied connector covers must remain on the unused interfaces during operation!

against mechanically active substances / conformity with EN 60721-3-3	Yes ; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Operating systems	
Operating system	Windows CE
Configuration	
Message indicator	Yes
With alarm logging system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe administration	Yes
Configuration software	
Configuration tool	WinCC flexible Compact Version 2005 or higher (to be ordered separately)
2nd configuration kit	WinCC flexible Compact
Version	Version 2005
Configuration tool	WinCC flexible
Type	Compact
Languages	
Online languages	
Number of online/runtime languages	5
Languages	
Languages per project	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Task planner	Yes
Help system	Yes
Number of characters per info text	70
Message system	
Number of alarm classes	32
Number of messages	2000
Bit messages	Yes
Analog messages	Yes
Number of bit messages	2000
Number of analog messages	50
Telegram message procedure Alarm S	No
System messages HMI	Yes
System messages PLC	Yes
System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	No

Message length (in characters)	80
Lines	1
Number of process values per message	8
Acknowledgment groups	99
Message indicator	Yes
Acoustic feedback	No
First/last value	Yes
Recipe administration	
Number of recipes	100
Data records per recipe	200
Entries per data record	200
Recipe memory	32 KB integrated Flash, expandable
Variables	
Number of variables per device	1000
Number of variables per screen	50
Number of variables	1000
Initial values	1000
Limit values	Yes
Multiplexing	Yes
Structs	No
Type Date & Time	1000
Images	
Number of configurable images	500
Permanent window/default	Yes
Start screen configurable	Yes
Image selection by PLC	Yes
Image number in the PLC	Yes
Image objects	
Text objects	2,500 text elements
Fields per image	50
Date/time fields	30
Index of screen context	No
Return	Yes
Graphics object	Bit maps, icons, icon (full-screen), vector graphics
Icons	500
Icon (full screen)	50
Complex image objects	
Status/control	With SIMATIC S7
dynamic objects	Diagrams, bar graphs, sliders, analog display, invisible buttons

Number of objects per project	500
Number per image	5
Methods	Trend
Limit value lines	Yes
Number of bars per chart	5
Limit value lines	Yes
alphanumeric fields	1000
alphanumeric fields per image	100
numerical fields	1000
numerical fields per image	100
Password errors	1000
Number of slides per image	0
Number of analog indicators per image	0
Number of visible switches per project	1000
visible switches per image	100
hidden switches per image	100
Number of status switches per project	1000
Button status switches per image	100
Number of selector switches per project	1000
Selector switches per image	100
Number of decade switches per project	0
Decade switches per image	0
Number of signal lamps per project	1000
Signal lamps per image	100
Attributes for dynamic objects	
Color change	Yes
X/Y movement	Yes
Hide	Yes
Angle of turn	No
Lists	
Number of text lists per project	300
Number of text lists per image	10
Number of entries per text list	30
Number of graphics lists per project	100
Number of graphic lists per image	10
Number of entries per graphics list	30
Security	
Number of user groups	50
Number of user rights	32

Password export/import	Yes
Data carrier support	
PC card	No
CF card	No
Logging through printer	
Recording/Printing	Alarms, report (shift report), color print, hardcopy
Transfer (upload/download)	
Transfer of configuration	MPI/PROFIBUS DP, serial, USB, Ethernet, by means of external storage medium, automatic transfer recognition
Process coupling	
Connection to controller	S5, S7-200, S7-300/400, Win AC, PC (TCP/IP), SINUMERIK, SIMOTION, Allen Bradley (DF1), Mitsubishi (FX), Telemecanique (ADJUST), Modicon (Modbus), further non-Siemens drivers, see chapter "System interfaces"
S7-200	Yes
PPI (point-to-point)	Yes
PPI network	No
MPI	Yes
PROFIBUS DP	Yes
S7-300/400	Yes
MPI	Yes
PROFIBUS DP	Yes
PROFINET	Yes
S5	Yes ; only PROFIBUS DP
serial	No
PROFIBUS DP	Yes
TI 505	No
Allen Bradley (DF1)	Yes
Allen Bradley (DF485)	No
Mitsubishi (FX)	Yes
Telemecanique (ADJUST)	Yes
OMRON (LINK/Multilink)	No
Modicon (Modbus)	Yes
Functions	
Key repeat	No
TAB sequence	Yes
Calculating functions	Yes
Animate	Yes
Menu tree editor	Yes
Unit switchover	No

Service tools/configuration aids	
Clean screen	Yes
Touch calibration	Yes
Backup/restore	Yes
Simulation	Yes
Device switchover	Yes
Delta transfer	Yes
Monitoring function for battery and memory	No
Trace (operation archive)	No
Expandability/openness	
Open Platform Program	Yes
I/O / Options	
I/O devices	Printer
MultiMediaCard	Yes
Additional software components loadable	Yes
Dimensions	
Front of enclosure (W x H)	212 mm x 156 mm
Weights	
Weight (without packaging)	0.8 kg
other	
free hotline	Yes
Warranty period	1 a
Status	Sep 11, 2014