

product type designation



Figure similar

SIPLUS ET 200SP CP 1542SP-1 IRC TX RAIL

SIPLUS ET 200SP CP 1542SP-1 IRC TX rail based on 6GK7542-6VX00-0XE0 with conformal coating, -40...+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), for connection of a SIMATIC S7-ET 200SP to Industrial Ethernet, SINAUT ST7, TeleControl Server Basic, IEC-60870-5-104 or DNP3 protocol to a control center; open IE communication (TCP/IP, ISO-on-TCP, UDP), IP broadcast/multicast, SNMPV1 DHCP, secure email, IPv4/IPv6, support of SINEMA Remote Connect

transfer rate	
transfer rate	
• at the 1st interface	10 ... 100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
• at the 1st interface / according to Industrial Ethernet	2
type of electrical connection	
• at the 1st interface / according to Industrial Ethernet	via ET 200SP bus adapter (RJ45, FC, SCRJ), integrated switch
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage	24 V
supply voltage	19.2 ... 28.8 V
power loss [W]	6 W
ambient conditions	
ambient temperature	
• for vertical installation / during operation	-40 ... +50 °C
• for horizontally arranged busbars / during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
• note	+85 °C for 10 min (OT4, ST1/ST2 according to EN 50155)
installation altitude / at height above sea level / maximum	2000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
relative humidity	
• with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
• conformity according to EN 60721-3-5	Yes; Class 5B2 mold and fungal spores (excluding fauna), Class 5B3 on request
resistance to chemically active substances	
• conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
• conformity according to EN 60721-3-5	Yes; Class 5C3 (RH < 75%) including salt spray acc. to EN 60068-2-52 (Severity level 3). The supplied plug covers must remain in place over the unused interfaces during operation!

resistance to mechanically active substances	
conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
conformity according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of coating / for electronic devices in railway applications according to EN 50155	Yes; Protective coating of the Class PC2 according to EN 50155:2017
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
width	60 mm
height	117 mm
depth	74 mm
net weight	0.18 kg
fastening method	
35 mm top hat DIN rail mounting	Yes
product features, product functions, product components / general	
number of units	
- per CPU / maximum - note	2 2 CPUs can be plugged in per CPU, simultaneous operation with BA Send and CM DP is possible
performance data / open communication	
number of possible connections / for open communication	
by means of T blocks / maximum	32
data volume	
as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum	65536 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
- maximum - with OP connections / maximum	16 16
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	32
performance data / IT functions	
number of possible connections	
as email client / maximum	1
performance data / telecontrol	
suitability for use	
- node station - substation - TIM control center	No Yes No
control center connection	
- by means of a permanent connection - by means of demand-oriented connection - note	IEC 60870-5, DNP3, (Modbus TCP by block solutions of the CPU) capable control stations, connection to Telecontrol Server Basic and ST7 capable control station supported supported Connection to SCADA system by IEC 60870-5 104, DNP3, Telecontrol Server Basic and ST7 capable control center
protocol / is supported	
- DNP3 - IEC 60870-5 - SINAUT ST7 protocol	Yes Yes Yes
product function / data buffering if connection is aborted	Yes; TCSB 64000 events, SINAUT ST7 32000 telegrams, DNP3 100000 events, IEC 60870-5 100000 events
number of data points per station / maximum	500
number of stations / for direct communication / with Telecontrol Server Basic	

• in send direction / maximum	3
• in receive direction / maximum	15
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
• SNMP v1	Yes
• SNMP v3	No
• DCP	Yes
• LLDP	Yes
configuration software	
• required	STEP 7 Professional V14 (TIA Portal) or higher
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function / web-based diagnostics	Yes; via ET 200SP CPU
product functions / security	
product function / with VPN connection	SINEMA RC
product function	
• blocking of communication via physical ports	Yes
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
• NTP	Yes
• NTP (secure)	No
time synchronization	
• from NTP-server	Yes
• from control center	Yes
standards, specifications, approvals	
certificate of suitability	
• fire protection in accordance with EN 45545-2	Yes; Railway vehicles - for proof, see Service & Support
railway application	
certificate of suitability	
• railway application in accordance with EN 50121-3-2	Yes; EMC for railway vehicles
• railway application in accordance with EN 50121-4	Yes; EMC for signal and telecommunication equipment
• railway application in accordance with EN 50124-1	Yes; Railway applications - Overvoltage category OV2 pollution degree PD2 rated impulse voltage UNi = 0.5 kVUNm = DC 24
• railway application in accordance with EN 50125-1	Yes; Railway vehicles - See ambient conditions
• railway application in accordance with EN 50125-2	Yes; Fixed-electrical installations - see ambient conditions
• railway application in accordance with EN 50125-3	Yes; Signal and telecommunications equipment - see Ambient conditions vibrations and shocks: Application point outside the rails (distance 1 m to 3 m from rail)
• railway application in accordance with EN 50155	Yes; Railway vehicles - temperature class OT4, ST1/ST2, horizontal mounting position
• railway application in accordance with EN 61373	Yes; Railway vehicles - Vibrations and shocks Category 1 Class A/B
further information / internet links	
internet link	
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available

and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----

[Miscellaneous](#)



[Manufacturer Declaration](#)



Railway

[Confirmation](#)

last modified: 3/22/2024