

No longer available SIMATIC IPC847C (Rack PC, 19", 4HU);
 Interfaces: 2 x Gbit LAN (RJ45) 1x DVI-I; audio; 2x COM; 1x LPT; 2x PS/2;
 4x USB 2.0 on rear, 2x USB 2.0 on the front; Temp. and fan monitoring;
 Watchdog, card retainer Core i7-610E (2C/4T, 2.53 GHz, 4 MB cache, TB,
 VT-X, VT-D, EM64-T, AMT); Mainboard without fieldbus RAID5 1 TB (3x
 500 GB HDD SATA, in removable frame, hot swap; front-side 8 GB DDR3
 SD-RAM, ECC (2x 4 GB), Dual channel DVD +/- RW; Bus module, 8 slots:
 7xPCI, 1x PCIE X16; DVI-VGA adapter for onboard graphics without
 operating system without software 110/230V industrial power supply unit
 with NAMUR, Power supply cable Europe

Supply voltage	
Type of supply voltage	100 - 240 V AC
Line frequency	
• Rated value 50 Hz	Yes
• Rated value 60 Hz	Yes
Processor	
Processor type	Core i7-610E (2.53 GHz 2C/4T, 4 MB Cache, TB, VT-x, VT-d, EM64T); Core i5-520E (2.4 GHz, 2C/4T, 3 MB Cache, TB, VT-x, VT-d, EM64T); Core i3-330E (2.13 GHz, 2C/4T, 3 MB Cache, VT-x, EM64T)
Drives	
Hard disk	250 GB or 500 GB SATA HDD, RAID1/RAID5 HDD, 32 GB SATA SSD, installed internally on the drive carrier, in the shock and vibration- damped drive rack, or on the front drive support in the swap frame
Memory	
Type of memory	DDR3-SDRAM
Main memory	1 GB to 8 GB, ECC optional
Capacity of main memory, max.	8 Gbyte
Hardware configuration	
Slots	
• free slots	7x PCI, 1x PCIe (x16) or 7 x PCI, 3x PCIe (x4), 1x PCIe (x16) all modules up to 312 mm in length are supported
Interfaces	
Interfaces/bus type	2x COM, 1x LPT, 1x DVI-I, 2x PS/2, audio (Microphone In, Line Out), 7x USB 2.0, 2x Gigabit Ethernet, PROFIBUS or PROFINET optional
PROFIBUS/MPI	onboard, isolated, max. 12 Mbit/s, CP 5611-compatible
USB port	2x USB 2.0 on front, 4x USB 2.0 on rear, 1x USB 2.0 internal
Connection for keyboard/mouse	2x PS/2
serial interface	COM1: 1 x V.24 (RS 232), COM2: 1 x V.24 (RS 232C)
parallel interface	LPT1 (EPP/ECP)
Multimedia	
• Audio In/Out	Yes
• Microphone In	Yes
Video interfaces	
• Graphics interface	1 x DVI-I or 1 x VGA (via adapter) optional
Industrial Ethernet	
• Industrial Ethernet interface	2x Ethernet (RJ45)
— 100 Mbps	Yes
— 1000 Mbps	Yes
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
• Watchdog	Yes
• Status LEDs	POWER; HARD DISK; ETHERNET 1; ETHERNET 2; PN I MPI/DP; WATCHDOG; TEMP; HDD1 ALARM; HDD2 ALARM; HDD3 ALARM
Ambient conditions	

Ambient temperature during operation	
• Ambient temperature during operation	+5 °C to +35 °C without restrictions, +5 °C to +45 °C no burner operation, +5 °C to +50 °C no ODD operation, power dissipation of the expansion modules in total less than 30 W
Relative humidity	
• Relative humidity	Tested according to IEC 60068-2-78, IEC 60068-2-30: 5% to 80% at 25 °C (no condensation)
Vibrations	
• Vibration resistance during operation acc. to IEC 60068-2-6	Tested according to IEC 60068-2-6: 10 cycles, 10 Hz to 58 Hz: 0.0375 mm, 58 Hz to 500 Hz: 4.9 m/s ² (0.5 g)
Shock testing	
• Shock load during operation	Tested according to IEC 60068-2-27, IEC 60068-2-29: half-sine: 50 m/s ² (5 g), 30 ms, 100 shocks per axis
Operating systems	
pre-installed operating system	Windows XP Professional, 32-bit, MUI; Windows 7 Ultimate, 32-bit, MUI; Windows Server 2008 Standard Edition incl. 5 Clients, 32-bit, MUI
Additional info on operating system	Multi-Language User Interface (MUI): 5 languages (English, German, French, Spanish, Italian)
Software	
SIMATIC Software	Optional in a package with SIMATIC WinCC, WinCC flexible, or WinAC RTX

last modified:

2/16/2022 