

SIMATIC IPC427E (Microbox PC), HD graphic onboard, 4x USB V3.0 (high current), PCIE (optional), Core i5-6442EQ; 3x Gbit Ethernet (IE/PN); Mounting onto standard rail; 8 GB; Without RS232/485, without PCIe; Windows 10 Enterprise 2019 LTSC (64-bit), MUI (en,de,fr,it,es), for Celeron, i3 and i5, Without replaceable mass storage; 240 GB solid-state drive SATA Without SIMATIC software; 24 V DC industrial power supply

| General information                                       |                                                                                                                                                                                                            |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product type designation                                  | IPC427E                                                                                                                                                                                                    |
| Installation type/mounting                                |                                                                                                                                                                                                            |
| Mounting                                                  | DIN rail, wall mounting, portrait mounting                                                                                                                                                                 |
| Design                                                    | Box PC, built-in unit                                                                                                                                                                                      |
| Supply voltage                                            |                                                                                                                                                                                                            |
| Type of supply voltage                                    | 24 V DC                                                                                                                                                                                                    |
| Mains buffering                                           |                                                                                                                                                                                                            |
| • Mains/voltage failure stored energy time                | 20 ms                                                                                                                                                                                                      |
| Processor                                                 |                                                                                                                                                                                                            |
| Processor type                                            | Celeron G3902 (2C/2T, 1.6 GHz, 2 MB Cache); Core i3-6102E (2C/4T, 1.9 GHz, 3 MB Cache); Core i5-6442EQ (4C/4T, 1.9 (2.7) GHz, 6 MB Cache, iAMT); Xeon E3-1505L v5 (4C/8T, 2.0 (2.8) GHz, 8 MB Cache, iAMT) |
| Chipset                                                   | Intel C236 / Intel H110                                                                                                                                                                                    |
| Graphic                                                   |                                                                                                                                                                                                            |
| Graphics controller                                       | Intel HD graphics controller                                                                                                                                                                               |
| Drives                                                    |                                                                                                                                                                                                            |
| Optical drives                                            | possible as external drive via USB                                                                                                                                                                         |
| Hard disk                                                 | 2.5" SATA ≥ 320 GB                                                                                                                                                                                         |
| SSD                                                       | Yes; 128 / 240 / 480 GB                                                                                                                                                                                    |
| Memory                                                    |                                                                                                                                                                                                            |
| Type of memory                                            | DDR4-2400 SO-DIMM                                                                                                                                                                                          |
| Main memory                                               | 4 / 8 / 16 GB, ECC optional                                                                                                                                                                                |
| Capacity of main memory, max.                             | 16 Gbyte                                                                                                                                                                                                   |
| Data areas and their retentivity                          |                                                                                                                                                                                                            |
| Retentive data area (incl. timers, counters, flags), max. | 512 kbyte; 128 KB can be stored in the buffer time; optional                                                                                                                                               |
| Hardware configuration                                    |                                                                                                                                                                                                            |
| Slots                                                     |                                                                                                                                                                                                            |
| • free slots                                              | 2x PCIe; optional: 1x PCIe (x4); 2x PCIe (x1, x4), with card retainer                                                                                                                                      |
| • Number of PCI slots                                     | 2; Optional                                                                                                                                                                                                |
| • Number of compact flash slots                           | 1; CFast                                                                                                                                                                                                   |
| Interfaces                                                |                                                                                                                                                                                                            |
| Number of industrial Ethernet interfaces                  | 3; Ethernet (2x RJ45, optional 3x RJ45)                                                                                                                                                                    |
| USB port                                                  | 4x USB 3.0                                                                                                                                                                                                 |
| Connection for keyboard/mouse                             | USB / USB                                                                                                                                                                                                  |
| serial interface                                          | Without / 2x COM (RS 232 / 485 / 422; switchable)                                                                                                                                                          |
| Video interfaces                                          |                                                                                                                                                                                                            |
| • Graphics interface                                      | 2x DisplayPort                                                                                                                                                                                             |
| Industrial Ethernet                                       |                                                                                                                                                                                                            |
| • Industrial Ethernet interface                           | 3x Ethernet (RJ45)                                                                                                                                                                                         |
| — 100 Mbps                                                | Yes                                                                                                                                                                                                        |
| — 1000 Mbps                                               | Yes                                                                                                                                                                                                        |
| Interrupts/diagnostics/status information                 |                                                                                                                                                                                                            |
| Bus diagnostics                                           | Yes                                                                                                                                                                                                        |
| Integrated Functions                                      |                                                                                                                                                                                                            |

|                                                                            |                                                                                                                                                                                      |
|----------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Monitoring functions</b>                                                |                                                                                                                                                                                      |
| • Temperature monitoring                                                   | Yes                                                                                                                                                                                  |
| • Watchdog                                                                 | Yes                                                                                                                                                                                  |
| • Status LEDs                                                              | 1x power, 3x user                                                                                                                                                                    |
| • Fan                                                                      | No                                                                                                                                                                                   |
| • Monitoring function via network                                          | Optional                                                                                                                                                                             |
| <b>EMC</b>                                                                 |                                                                                                                                                                                      |
| <b>Interference immunity against discharge of static electricity</b>       |                                                                                                                                                                                      |
| • Interference immunity against discharge of static electricity            | ±6 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2                                                                                             |
| <b>Interference immunity against high-frequency electromagnetic fields</b> |                                                                                                                                                                                      |
| • Interference immunity against high frequency radiation                   | 10 V/m for 80 - 1 000 MHz and 1.4 - 2 GHz, 80% AM acc. to IEC 61000-4-3; 3 V/m for 2 - 2.7 GHz, 80% AM acc. to IEC 61000-4-3; 10 V for 10 kHz - 80 MHz, 80% AM acc. to IEC 61000-4-6 |
| <b>Interference immunity to cable-borne interference</b>                   |                                                                                                                                                                                      |
| • Interference immunity on supply cables                                   | ±2 kV acc. to IEC 61000-4-4, burst; ±1 kV acc. to IEC 61000-4-5, surge symmetric; ±2 kV acc. to IEC 61000-4-5, surge asymmetric                                                      |
| • Interference immunity on signal cables >30m                              | ±2 kV acc. to IEC 61000-4-5, surge, length > 30 m                                                                                                                                    |
| • Interference immunity on signal cables < 30m                             | ±1 kV acc. to IEC 61000-4-4; burst; length < 3 m; ±2 kV acc. to IEC 61000-4-4; burst; length > 3 m                                                                                   |
| <b>Interference immunity against voltage surge</b>                         |                                                                                                                                                                                      |
| • asymmetric interference                                                  | ±2 kV acc. to IEC 61000-4-5, surge asymmetric                                                                                                                                        |
| • symmetric interference                                                   | ±1 kV acc. to IEC 61000-4-5, surge symmetric                                                                                                                                         |
| <b>Interference immunity to magnetic fields</b>                            |                                                                                                                                                                                      |
| • Interference immunity to magnetic fields at 50 Hz                        | 100 A/m; to IEC 61000-4-8                                                                                                                                                            |
| <b>Emission of conducted and non-conducted interference</b>                |                                                                                                                                                                                      |
| • Interference emission via line/AC current cables                         | EN 61000-6-3, EN 61000-6-4, CISPR 22 Class B, FCC Class A                                                                                                                            |
| <b>Degree and class of protection</b>                                      |                                                                                                                                                                                      |
| IP degree of protection                                                    | IP20                                                                                                                                                                                 |
| <b>Standards, approvals, certificates</b>                                  |                                                                                                                                                                                      |
| CE mark                                                                    | Yes                                                                                                                                                                                  |
| UL approval                                                                | Yes                                                                                                                                                                                  |
| • UL 508                                                                   | Yes                                                                                                                                                                                  |
| cULus                                                                      | Yes                                                                                                                                                                                  |
| RCM (formerly C-TICK)                                                      | Yes                                                                                                                                                                                  |
| KC approval                                                                | Yes                                                                                                                                                                                  |
| EAC (formerly Gost-R)                                                      | Yes                                                                                                                                                                                  |
| FCC                                                                        | Yes                                                                                                                                                                                  |
| EMC                                                                        | CE, EN 55022A, EN 61000-6-4, EN 61000-6-2                                                                                                                                            |
| <b>Use in hazardous areas</b>                                              |                                                                                                                                                                                      |
| • ATEX Zone 2                                                              | Yes; Optional                                                                                                                                                                        |
| • IECEx Zone 2                                                             | Yes; Optional                                                                                                                                                                        |
| • cULus Class I Zone 2, Division 2                                         | Yes; Optional                                                                                                                                                                        |
| <b>Marine approval</b>                                                     |                                                                                                                                                                                      |
| • Germanischer Lloyd (GL)                                                  | Yes                                                                                                                                                                                  |
| • American Bureau of Shipping (ABS)                                        | Yes                                                                                                                                                                                  |
| • Bureau Veritas (BV)                                                      | Yes                                                                                                                                                                                  |
| • Det Norske Veritas (DNV)                                                 | Yes                                                                                                                                                                                  |
| • Korean Register of Shipping (KRS)                                        | Yes                                                                                                                                                                                  |
| • Lloyds Register of Shipping (LRS)                                        | Yes                                                                                                                                                                                  |
| • Nippon Kaiji Kyokai (Class NK)                                           | Yes                                                                                                                                                                                  |
| <b>Ambient conditions</b>                                                  |                                                                                                                                                                                      |
| <b>Ambient temperature during operation</b>                                |                                                                                                                                                                                      |
| • Ambient temperature during operation                                     | 0 °C to 55 °C                                                                                                                                                                        |
| <b>Ambient temperature during storage/transportation</b>                   |                                                                                                                                                                                      |
| • min.                                                                     | -40 °C                                                                                                                                                                               |
| • max.                                                                     | 70 °C                                                                                                                                                                                |
| <b>Relative humidity</b>                                                   |                                                                                                                                                                                      |
| • Relative humidity                                                        | Tested according to IEC 60068-2-78, IEC 60068-2-30: Operation: 5% to 80% at 25 °C (no condensation), Storage: 5% to 95% at 25 °C (no condensation)                                   |

|                                                                                                               |                                                                                                         |
|---------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>Vibrations</b>                                                                                             |                                                                                                         |
| <ul style="list-style-type: none"> <li>Vibration resistance during operation acc. to IEC 60068-2-6</li> </ul> | tested to DIN IEC 60068-2-6: 10 Hz to 58 Hz: 0.075 mm, 58 Hz to 200 Hz: 9.8 m/s <sup>2</sup> (1 g)      |
| <b>Shock testing</b>                                                                                          |                                                                                                         |
| <ul style="list-style-type: none"> <li>Shock load during operation</li> </ul>                                 | Tested to DIN IEC 60068-2-29: 50 m/s <sup>2</sup> (5 g), 30 ms, 100 shocks                              |
| <b>Operating systems</b>                                                                                      |                                                                                                         |
| pre-installed operating system                                                                                | Windows 7 Ultimate (Multi-Language) 64-bit, Windows Embedded Standard 7 E/P 32-bit / 64-bit, Windows 10 |
| without operating system                                                                                      | Yes; Optional                                                                                           |
| pre-installed operating system                                                                                |                                                                                                         |
| <ul style="list-style-type: none"> <li>Windows 7</li> </ul>                                                   | Yes; Ultimate 32 bit or 64 bit                                                                          |
| <ul style="list-style-type: none"> <li>Windows 10 Enterprise</li> </ul>                                       | Yes; Windows 10 Enterprise 2016 LTSP, 64 bit, MUI                                                       |
| <b>Software</b>                                                                                               |                                                                                                         |
| SIMATIC Software                                                                                              | Optionally with pre-installed SIMATIC WinCC RT Advanced / Software Controller CPU 1500S software bundle |
| <b>Dimensions</b>                                                                                             |                                                                                                         |
| Width                                                                                                         | 262 mm                                                                                                  |
| Height                                                                                                        | 139.7 mm                                                                                                |
| Depth                                                                                                         | 55.5 mm                                                                                                 |
| <b>last modified:</b>                                                                                         | 6/4/2021               |