

SERVICE SET FOR TP 070, TP 170A/B,
OP 170B, TP 170MICRO, OP /TP 270 6",
MP 177 6"T,
MP 270B 6" TOUCH AMOUNT AND CONTENT: SEE
TECHNICAL DATA



Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Operating temperature	
Operating temperature range, min.	0 °C
Operating temperature range, max.	55 °C
Storage/transport temperature	
min.	-20 °C
max.	70 °C
Relative humidity	
Operation, max.	95 %
Scope of supply	
Number of sets	1 ; Content: 3 x mounting seal, 2 x labeling strip, 7 x plastic mounting clip, 20 x aluminum mounting clip, 1 x 2-pin female connector
Other	
Note:	for TP 070, TP 170A/B, OP 170B, TP 170micro, OP /TP 270 6", MP 177 6"T, MP 270B 6" Touch
Usable in the following products	
Product 1	6AV6545-0AA15-2AX0

Product 2	6AV6545-0BC15-2AX0
Product 3	6AV6542-0BB15-2AX0
Product 4	6AV6640-0CA01-0AX0
Product 5	6AV6542-0CA10-0AX0
Product 6	6AV6542-0CA10-0AX1
Product 7	6AV6545-0CA10-0AX0
Product 8	6AV6642-0EA01-3AX0
Product 9	6AV6545-0AH10-0AX0

Status

Jul 21, 2014