




SIMATIC WINCC V7.0 SP3 ASIA,
RC 128 (128 POWER TAGS),
RUNTIME & CONFIGURATION SW, ON DVD,
FLOATING LICENSE,
5 LANGUAGES (EN,CHS,CHT,KOR,JPN),
EXEC. UNDER XPPROF/ WINDOWS7 (32/64BIT)

General information	
Multi-user system	
Multi-user capability	Yes
Number of servers, max.	12
Number of clients for server without operator console, max.	32
Web clients	Yes
Operator control and monitoring	
Object block library	Yes ; Integrated
With alarm logging system (incl. buffer and acknowledgment)	Yes ; Integrated
Report system/log system	Yes
SQL database	Yes ; Integrated
Process diagnostics	No
Sector-specific and technological expansions	Yes
Recipes	
User archive/recipe management	Yes
Interfaces	
Programming interfaces	Yes
OPC-DA interface, Server	Yes

OPC-DA interface, Client	Yes
Hardware requirements	
Processor clock frequency, min.	1 GHz
Main memory, min.	1000 Mbyte
Configuration	
Max. number of multiusers configuration	32
Online configuration	Yes
Script languages (Runtime)	
Number of Visual Basic Scripts	Yes
other	Yes
Know-how protection	
Password protection	Yes
Languages	
Configuration languages	
Number of configuration languages	70
Status	Jul 14, 2014