

*** SPARE PART*** SIMATIC MP270B 6" TOUCH MULTI PANEL
5.7" TFT DISPLAY 4 MB CONFIGURING MEMORY,
CONFIGURABLE WITH WINCC FLEXIBLE STANDARD V1.0 OR
HIGHER



Display	
Design of display	TFT, 256 colors
Screen diagonal	5.7 in
Color type	Colors
Resolution (pixels)	
• Resolution (WxH in pixel)	320 x 240
• Horizontal image resolution	320 Pixel
• Vertical image resolution	240 Pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Touch screen
Keyboard fonts	
• Membrane keyboard	No
— user-definable label membrane keys	No
• Function keys	No
— Number of function keys with LEDs	0
• System keys	No

• Numeric/alphabetical input — hexadecimal keyboard • Multi-key operation — Number of multi-key operations	Yes / Yes Yes No 0
Connection type	
• Connection for mouse/keyboard/barcode reader	USB / USB / USB
Special operator controls	
• Illuminated pushbutton	Yes
Installation type/mounting	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
UPS connectable (serial)	Yes
Input current	
Current consumption (rated value)	0.75 A
Starting current inrush I _p t	0.5 A ² ·s
Power	
Power consumption, typ.	18 W
Processor	
Processor type	RISC 32-bit
Drives	
Diskette drive	No
CD-ROM	No
Hard disk	No
Memory	
Type of memory	Flash / RAM
Memory available for user data	4 096 kbyte
Battery	
Backup battery	
• Backup battery • Backup time, min.	optional 3.6 V 3 y
Type of output	
Info LED	No
Power LED	No
Error LED	No
Time of day	
Clock	

- Type
- retentive
- synchronizable

Hardware clock, battery backup, synchronizable
Yes
Yes

Interfaces

Interfaces/bus type	2 x RS232, 1 x RS422, 1 x RS485, 1 x Ethernet (RJ45) (max. 12 Mbit/s)
Number of RS 485 interfaces	1
• Transmission rate, max.	12 Mbit/s
USB port	1 x USB
PC card slot	1 x PC card slot
CF card slot	1 x CF card slot
Industrial Ethernet	
• Industrial Ethernet interface	1 x Ethernet (RJ45)

Degree and class of protection

Front	IP65
IP (at the front)	IP65
IP (rear)	IP20

Standards, approvals, certificates

Certifications	CE, GL, ABS, DNV, LRS, FM Class I Div. 2, cULus, EX Zone 2/22, C-TICK
----------------	---

Ambient conditions

Free fall	
• Fall height, max.	90 m
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	90 %

Operating systems

Operating system	Windows CE
------------------	------------

Configuration

Configuration software	
• Configuration tool	WinCC flexible Standard Version 2004 and higher (to be ordered separately)
• 2. Configuration kit	WinCC flexible Standard
— Version	Version 2004
— Configuration tool	WinCC flexible
— Type	Standard

Languages

Online languages	
------------------	--

• Number of online/runtime languages	5
Project languages	
• Languages per project	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Number of Visual Basic Scripts	
• Debugging in the simulator	No
Task planner	Yes
Help system	Yes
• Number of characters per info text	70
• Number of tooltips	0
Message system	
• Number of alarm classes	32
• Number of messages	4 000
• Bit messages	Yes
— Number of bit messages	4 000
• Analog messages	Yes
— Number of analog messages	4 000
• Telegram message procedure Alarm S	Yes
• System messages HMI	Yes
• System messages PLC	Yes
• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	Yes
• Message length (in characters)	70
• Lines	1
• Number of process values per message	8
• Acknowledgment groups	
— Number of acknowledgement groups	Yes
• Message indicator	Yes
• acoustic feedback	No
• First/last value	Yes
Recipe administration	
• Number of recipes	300
• Data records per recipe	500
• Entries per data record	1 000
• Recipe memory	64 KB integrated Flash, expandable
Variables	
• Number of variables per device	2 048
• Number of variables per screen	200
• Number of variables	2 048
• Limit values	Yes

• Multiplexing	Yes
• Structures	Yes
• Type Date & Time	2 048
Images	
• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	10,000 text elements
• Number of I/O fields per image	200
• Number of date/time fields	200
• Index of screen context	No
• Return	Yes
• Graphics object	Bit maps, icons, vector graphics
— Icons	1 000
— Icon (full screen)	0
Complex image objects	
• Status/control	With SIMATIC S7
• dynamic objects	Diagrams, bar graphs, sliders, analog display, invisible buttons
— Number of objects per project	1 000
— Number of curve diagrams per image	10
• Methods	Trend / profile
• Limit value lines	Yes
• Number of bars per chart	10
• Limit value lines	Yes
• alphanumeric fields	300
• alphanumeric fields per image	200
• numerical fields	2 048
• numerical fields per image	200
• Password fields	2 048
• Number of slides per image	10
• Number of analog indicators per image	10
• Number of visible switches per project	200
• visible switches per image	200
• hidden switches per image	200
• Number of status switches per project	200
• Number of status switches per image	200
• Number of selector switches per project	200
• Selector switches per image	200

• Number of decade switches per project	200
• Decade switches per image	200
• Number of signal lamps per project	200
• Signal lamps per image	200
Attributes for dynamic objects	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
• Angle of rotation	No
Lists	
• Number of text lists per project	500
• Number of entries per text list	256
• Number of graphics lists per project	400
• Number of graphic lists per image	200
• Number of entries per graphics list	256
Archiving	
• Number of archives per device	20
• Number of measuring points per project	20
• Number of entries per archive	10 000
• Message archive	Yes
• Process value archive	Yes
• Archiving methods	Sequence archive, circular log, alarm log, process value archive
— Sequential archive	Yes
— Short-term archive	Yes
• Memory location	PC card, CF card, Ethernet
— PC card	Yes
— CF card	Yes
— USB memory	No
— Ethernet	Yes
• Data storage format	CSV file, readable, e.g. with MS Excel, MS Access
— CSV	Yes
— TXT	No
• external evaluation	Readable, e.g. with MS Excel, MS Access, etc.
• Size of archive	depending on free memory on ext. card/stick or on free hard disk space via network drive
• Online evaluation	via trends
— using trend curves	Yes
Filters	
• cyclic	Yes
• Tolerance	Yes
• Change	Yes
Security	

• Number of user groups	50
• Number of user rights	32
• Password export/import	Yes
Data carrier support	
• PC card	Yes
• CF card	Yes
• Diskette drive	No
• Hard disk	No
• CD-ROM	No
Logging through printer	
• Recording/Printing	Alarms, report (shift report), color print, hardcopy
Transfer (upload/download)	
• Transfer of configuration	MPI/PROFIBUS DP, serial, USB, Ethernet, by means of external storage medium, automatic transfer recognition
Process coupling	
• Connection to controller	S5, S7-200, S7- 300/400, TI 505, Win AC, PC (TCP/IP), SINUMERIK, SIMOTION, Allen Bradley (DF1), Allen Bradley (DF485), Mitsubishi (FX), Telemecanique (ADJUST), OMRON (LINK/Multilink), Modicon (Modbus), for further non-Siemens drivers, see section on "System interfaces"
• S7-200	Yes
— PPI (point-to-point)	Yes
— PPI network	Yes
— MPI	Yes
— PROFIBUS DP	Yes
• S7-300/400	Yes
— MPI	Yes
— PROFIBUS DP	Yes
— PROFINET	Yes
• S5	Yes
— serial	Yes
— PROFIBUS DP	Yes
• TI 505	Yes
• Allen Bradley (DF1)	Yes
• Allen Bradley (DF485)	Yes
• Mitsubishi (FX)	Yes
• Mitsubishi (MP4)	Yes
• Telemecanique (ADJUST)	Yes
• Telemecanique (Uni-Telway)	Yes
• OMRON (LINK/Multilink)	Yes
• Modicon (Modbus)	Yes
• GE-Fanuc (SNP)	Yes

Functions	
• Key repeat	No
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	Yes
• Menu tree editor	No
• Unit switchover	No
Service tools/configuration aids	
• Clean screen	Yes
• Touch calibration	Yes
• Backup/Restore manually	Yes
• Simulation	Yes
• Device switchover	Yes
• Delta transfer	Yes
• Monitoring function for battery and memory	Yes
• Trace (operation archive)	No
Expandability/openness	
• Open Platform Program	Yes
Peripherals/Options	
Peripherals	Printer, barcode reader
• SIMATIC HMI MM memory card: Multi Media Card	No
• SIMATIC HMI SD memory card: Secure Digital memory card	No
• USB memory	No
Dimensions	
Width of the housing front	212 mm
Height of housing front	156 mm
Weights	
Weight (without packaging)	1 kg
Other	
free hotline	Yes
Warranty period	1 y
last modified:	22.06.2016